


**Product features and key data**

<b>Applications</b>	Damp environments canopied outdoor areas
<b>Luminaire type</b>	LED weather-proof surface-mounted luminaire IP66.
<b>Mounting method</b>	Suspension Surface-mounting
<b>Luminaire optic</b>	Polycarbonate diffuser with inner prism structure.
<b>Connected load</b>	28 W
<b>Colour temperature</b>	4.000 K
<b>Rated luminous flux</b>	3.900 lm
<b>Luminous efficacy</b>	139 lm/W
<b>CEN flux code</b>	56 85 95 93 100 0 0 11 7
<b>Service life</b>	L80 (25 °C) = 50.000 h
<b>Colour rendering index</b>	80
<b>Colour tolerance</b>	3 SDCM
<b>Photobiological class</b>	Group 1- no risk
<b>Luminaire colour</b>	RAL7035 Light grey
<b>Luminaire body</b>	Luminaire body of PC.
<b>Electrical version</b>	With electronic transformer, digitally dimmable (DALI).
<b>Wiring</b>	5LV
<b>Wire diameter</b>	2,50 mm <sup>2</sup>
<b>Monitoring Ready</b>	Yes
<b>Ingress Protection (IP) rating</b>	IP66
<b>Protection rating on room side</b>	IP66
<b>Protection class</b>	I
<b>Impact resistance (IK)</b>	IK08
<b>Hot wire resistance</b>	650 °C
<b>Ambient temperature</b>	-20 - 35 °C
<b>Net length</b>	1.552 mm
<b>Net width</b>	102 mm
<b>Net height</b>	91 mm
<b>Weight</b>	2,8 kg







**light distribution curve**



TX056194  
 UGR I = 22,8  
 UGR q = 18,2  
 DIN 5040: A40  
 UTE: 0,93 D + 0,07 T

■ C0 - C180  
 ■ C90 - C270

**Available accessories**

Material	Description
<b>ZBSB</b> 6923200	Steel strip suspension, length 1 m, of stainless steel (1 pair).
<b>ZBATL2</b> 6923300	Theft protection (mandatory for wall mounting).
<b>ZBMC</b> 6923400	Bracket for suspended mounting.
<b>Diffuser OleveonF 1.5 PC packed</b> 7130100	Replacement diffuser for Oleveon F 1.2 PMMA.
<b>Diffuser OleveonF 1.5 PMMA packed</b> 7130200	Replacement diffuser for Oleveon F 1.5 PMMA.
 <b>7650Fi OleveonF DALI L150 01</b> 7342500	Gear tray for E-Line Fix for integration of a weather-proof luminaire of type OleveonFit in a continuous line application. The clamps for tool-free quick mounting of the luminaire are mounted on the gear tray.
 <b>7650Fi OleveonF DALI L150 03</b> 7342600	Gear tray for E-Line Fix for integration of a weather-proof luminaire of type OleveonFit in a continuous line application. The clamps for tool-free quick mounting of the luminaire are mounted on the gear tray.
 <b>7650Fi OleveonF DALI L150 05</b> 7342700	Gear tray for E-Line Fix for integration of a weather-proof luminaire of type OleveonFit in a continuous line application. The clamps for tool-free quick mounting of the luminaire are mounted on the gear tray.
 <b>7750FI OleveonF DALI L150 01</b> 7344600	
 <b>7750FI OleveonF DALI L150 03</b> 7344700	
 <b>7750FI OleveonF DALI L150 05</b> 7344800	

**Offer text**

LED weather-proof surface-mounted luminaire IP66. Advantageous with applications requiring increased mechanical stability. Compliant to DIN 10500. The luminaires are suitable for applications in HACCP, IFS Version 6 and/or BRC Global Standard Food Version 7-certified companies in the food and beverage industries. Luminaire with limited surface temperature in accordance with DIN EN 60598-2-24, suitable for use in work locations exposed to fire hazards. For ceiling, wall and suspended mounting. Suspended mounting possible via optional accessories. Ceiling mounting with stainless steel fixing clips (included). Polycarbonate diffuser with inner prism structure. With symmetric wide light intensity distribution. Glare evaluation (EN 12464-1) according to UGR < 25. Luminaire luminous flux 3900 lm, connected load 28,00 W, luminous efficiency of luminaire 139 lm/W. Light colour neutral white, correlated colour temperature (CCT) 4000 K, general colour rendering index (CRI)  $R_a > 80$ . Mean rated service life  $L80(t_{90} 25^\circ\text{C}) = 50,000$  h. Luminaire body of PC. Colour of luminaire body light grey (RAL 7035). With clipless catch technology for protection rating-compliant and simple assembly of diffuser cover and luminaire body after electrical connection. Dimensions (L x W): 1552 mm x 102 mm, luminaire height 91 mm. Permissible ambient temperature (ta):  $-20^\circ\text{C} - +35^\circ\text{C}$ . Safety class (EN 61140): I, protection rating (DIN EN 60529): IP66, impact resistance level in accordance with IEC 62262: IK08, testing temperature of wire glow test in accordance with IEC 60695-2-11:  $650^\circ\text{C}$ . With 5-pole terminal to  $2.5\text{ mm}^2$ . With electronic transformer, digitally dimmable (DALI). The luminaire is monitoring-ready (MOR), supplies luminaire data for monitoring or for predictive maintenance and is therefore compatible to the TRILUX Digital Services (Energy Monitoring and Light Monitoring). The luminaire complies with fundamental requirements of applicable EU regulations and product safety legislation and bears the CE symbol. With integrated LiveLink WiFi RC radio receiver for integration into a LiveLink WiFi RC mesh network and DALI interface for possible signal forwarding. Radio signal range:  $> 20$  m. With 5-core through-wiring,  $1.5\text{ mm}^2$ .

**Accessories for the series:**

For horizontal wall mounting of the luminaire it is mandatory to install the ZBATL accessory (theft protection). ZBATL2, TOC 69 23 300