

LED SECURE




+ **Brida**
Clamp
Collier




APLICACIONES INDICADAS / SUITABLE APPLICATIONS / APPLICATIONS APPROPRIÉES




Temperatura ambiente: -25 a +45°C.
Ambient working temperature: -20 a +45°C.
Température de travail : -25 a +45°C.



IT - DE



RG1	MACADAM 3/4	UGR <19	CR>80	L70B50 > 50.000	IP68-2 IK10	CE	2014/34/EU II 3GD Ex nR II C T6 Gc Ex tc IIIC T85°C Dc
-----	----------------	------------	-------	-----------------------	----------------	----	---



Ref.	Potencia Power Puissance	Emisión bruta Gross output Flux de la source	Emisión Neta Net output Flux sortant	Tª color Tª colour Tª couleur	L	D	D + brida D + clamp D + fixations	Embalaje Packaging Emballage
	(W)	(Lm)	(Lm)	(°K)	(mm)	(mm)	(mm)	
LS113	13	1.490	997	3.000	727	83	133	1
LS114	13	1.550	1.037	4.000	727	83	133	1
LS123	16	2.560	1.712	3.000	727	83	133	1
LS124	16	2.670	1.786	4.000	727	83	133	1
LS213	24	2.980	1.993	3.000	1.337	83	133	1
LS214	24	3.200	2.140	4.000	1.337	83	133	1
LS223	32	5.120	3.424	3.000	1.337	83	133	1
LS224	32	5.340	3.571	4.000	1.337	83	133	1
LS313	29	3.720	2.488	3.000	1.637	83	133	1
LS314	29	4.000	2.675	4.000	1.637	83	133	1
LS323	40	6.310	4.220	3.000	1.637	83	133	1
LS324	40	6.700	4.481	4.000	1.637	83	133	1

ACCESORIOS LED SECURE / LED SECURE ACCESORIES / ACCESSOIRES LED SECURE

LÍNEA CONTINUA
CONTINUOUS LINE CONNECTION
CÂBLAGE TRAVERSANT

3 polos / 3 poles / 3 pôles

5 polos / 5 poles / 5 pôles

DALI

EMERGENCY
1h/3h

Ref. Q0978
Sujeción a báculo
Pole adapter
Adaptateur de lampadaire

