


PRODUCT DATASHEET PT-FIT 35/220...240 S

POWERTRONIC® PT-FIT S | ECG for HID lamps, for installation in luminaires



Areas of application

- Shop lighting
- Health and fitness areas (in luminaires with protection class IP66 or higher)
- Effect and accent lighting

Product benefits

- Optimized cost/benefit factor
- Compact dimensions and low weight for small luminaire designs
- Automatic safety shutdown of lamps in the event of a defect or at end of life (EoL)

Product features

- Energy Efficiency Index EEI: A2
- Supply voltage: 220...240 V
- Line frequency: 50...60 Hz
- RI suppression: to EN 55015/CISPR 15
- Safety: to EN 61347-2-12
- Line harmonics according to EN 61000-3-2
- Immunity according to EN 61547

TECHNICAL DATA

Electrical data


| | |
|--|--------------------|
| Nominal wattage | 43.00 W |
| Nominal voltage | 220...240 V |
| Nominal output voltage | 250 V |
| Input voltage AC | 198...264 V |
| U-OUT (working voltage) | 250 V |
| Type of current | AC |
| Inrush current | 30 A ¹⁾ |
| Mains frequency | 50/60 Hz |
| Power factor λ | 0.95 ²⁾ |
| ECG efficiency | 92 % |
| Max. ECG no. on circuit breaker 10 A (B) | 15 ³⁾ |
| Max. ECG no. on circuit breaker 16 A (B) | 26 ³⁾ |
| Operating frequency | 0.200...0.240 kHz |

¹⁾ $t_{width} = 150 \mu s$ (measured at 50 % I_{peak})

²⁾ Minimum

³⁾ Type B

Dimensions & Weight



| | |
|--------------------------------------|---|
| Length | 110.00 mm |
| Mounting hole spacing, length | 99,0 mm |
| Width | 75.00 mm |
| Height | 30.00 mm |
| Cable cross-section, input side | 0,5...1,0 mm ² / 0,5...1,5 mm ² ¹⁾ |
| Cable cross-section, output side | 0,5...1,0 mm ² / 0,5...1,5 mm ² ¹⁾ |
| Wire preparation length, input side | 8,5...9,5 mm |
| Wire preparation length, output side | 8,5...9,5 mm |
| Product weight | 245.00 g |

1) With ferrule / Without ferrule

Colors & materials

| | |
|-----------------|-------|
| Casing material | Metal |
| Body material | Metal |

Temperatures & operating conditions

| | |
|--|------------------------|
| Ambient temperature range | -15...+65 °C |
| Maximum temperature at tc test point | 85 °C |
| Max.housing temperature in case of fault | 110 °C |
| Permitted rel. humidity during operation | 5...85 % ¹⁾ |

1) Maximum 56 days/year at 85 %

Lifespan

| | |
|--------------|-----------------------|
| ECG lifetime | 30000 h ¹⁾ |
|--------------|-----------------------|

1) At maximum T_c / 10% failure rate

Capabilities

| | |
|--|---|
| Dimmable | No |
| Overheating protection | Power reduction and switch off at $T > 85$ °C at the tc point |
| Max. cable length to lamp/LED module | 1,5 m |
| Suitable for fixtures with prot. class | I |
| Suitable for emergency lighting | No |

Certificates & Standards

| | |
|---------------------------|---|
| Approval marks – approval | VDE / VDE-EMC / EAC / C-Tick |
| Standards | Acc. to EN 61347-2-12 / Acc. to EN 55015 / Acc. to EN 61000-3-2 / Acc. to EN 61547 |
| Protection class | I |
| Type of protection | IP20 |
| Energy efficiency class | A2 |
| EEL – Energy Label | A2 |

LOGISTICAL DATA

| | |
|------------------------------|--------------|
| Temperature range at storage | -40...+85 °C |
|------------------------------|--------------|











Safety advice

Ballast losses and lamp heat radiation can lead to heat accumulation in a completely closed case. Therefore it is necessary to ensure that the temperature at the measuring point t of the ECG does not exceed the maximum value.

Attention!

For safety reasons disconnect the device before replacing the lamp!

DOWNLOAD DATA

| DOWNLOAD DATA | |
|--|----------------------------|
|  | User instruction |
|  | User instruction |
|  | PRODUCT DATASHEET |
|  | Certificates |
|  | Certificates |
|  | Certificates |
|  | Declarations of conformity |
|  | Declarations of conformity |
|  | Declarations of conformity |
|  | Declarations of conformity |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4008321386632 | Shipping box 20 | 412 mm x 136 mm x 152 mm | 5169.89 g | 8.52 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.