







Our Ref.

288267-1

Product

Electronic control gear for LED module

Rating and principal characteristics

See page 2

Trade mark (if any)

Helvar

Type

LC35/2-DA-iC, LC35/2-DA-iC + LC1x70-SR, LC35/2-DA-iC HF, LC35/2-DA-iC HF + LC1x70-SR

Name and address of the licensee /

manufacturer

Helvar Oy Ab Keilaranta 5 FI-02150 ESPOO

FINLAND

Is in conformity with

EN 61347-2-13:2014 + FprA1:2016

EN 61347-1:2015

EN 62384:2006 + A1:2009

As shown in the Test Report(s)

No(s)

288267-1_A, 288267-1_B

It is authorized to use of the marks

ENEC 16 and FI

Validity

This certificate is valid until 21 April 2022 provided that the Conditions for ENEC and FI certification are met. This certificate includes the right to use the ENEC 16 and FI mark under the condition that product changes (if any) will be approved at SGS Fimko before the product is brought onto market.

Directive information

The certified product(s) fulfils requirements of above mentioned standard(s) which are harmonised under the Low Voltage Directive (2014/35/EU) at the date of issue of the certificate.

With the following limitations

Date of issue

21 April 2017

SGS Fimko Ltd

Signature

Kari Vesterinen

Product Line Manager



This certificate has 3 pages

Company of the compan

This certificate is issued by the company under its General Conditions for Certification Services accessible at http://www.sgs.fi/en/Terms-and-Conditions.aspx. Attention is drawn to the limitations of liability defined therein and in the Test Report here above mentioned which findings are reflected in this certificate. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Page No.: 2 of Certificate No.: ENEC/FI 2017034

Ratings and principal characteristics

LC35/2-DA-iC, LC35/2-DA-iC + LC1x70-SR: 220-240V, 0/50-60Hz, lout / Vout: 350mA / 12-50V or 700mA / 12-50V, tc 75°C, ta -20...+50°C, Uoutmax: 60V, Pout max: 35W, λ 0,92/0,96 (350/700mA)

LC35/2-DA-iC HF, LC35/2-DA-iC HF + LC1x70-SR: 220-240V, 0/50-60Hz, lout/Vout: 350mA / 40-50V or 700mA / 20-50V, tc 75°C, ta -20...+50°C, Uoutmax: 60V, Pout max: 17,5W (350mA) or 35W (700mA), λ 0,92/0,96 (350/700mA)

Additional information







This certificate is issued by the company under its General Conditions for Certification Services accessible at http://www.sqs.fi/en/Terms-and-Conditions.aspx. Attention is drawn to the limitations of liability defined therein and in the Test Report here above mentioned which findings are reflected in this certificate. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Page No.: 3 of Certificate No.: ENEC/FI 2017034

Manufacturing site(s)

Helvar Oy Ab Yrittäjäntie 23 FI-03600 KARKKILA, FINLAND





This certificate is issued by the company under its General Conditions for Certification Services accessible at http://www.sgs.fi/en/Terms-and-Conditions.aspx. Attention is drawn to the limitations of liability defined therein and in the Test Report here above mentioned which findings are reflected in this certificate. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

br