



<b>fitted with</b>	LED
<b>work equipment</b>	Energy efficiency category A++
<b>connected load</b>	electronic ballast
<b>power consumption</b>	220-240 V; 50/60 Hz
<b>power factor</b>	approx. 112 W
<b>luminous flux</b>	approx. 0,965
<b>luminous efficacy</b>	approx. 14050 lm
<b>light distribution</b>	approx. 125 lm/W
<b>direct ratio</b>	direct/indirect
<b>light colour</b>	approx. 12 %
<b>color rendering index (CRI)</b>	neutral white, approx. 4000 K
<b>consistent white light of</b>	> 80
<b>glare-free</b>	< 3 SDCM
<b>luminance</b>	conical prismatic screen
<b>unified glare rating</b>	< 3000 cd/m <sup>2</sup>
<b>technology</b>	< 10
<b>usage</b>	presence and daylight sensor control (PIR)
<b>luminaire body</b>	multi-function switch
<b>lamp cover</b>	steel/plastic, painted, silver metallic
<b>tubular section</b>	Acrylic satine
<b>luminaire base</b>	steel tube, painted, tubular section upright, silver metallic
<b>weight (net)</b>	C-form flat
<b>mains lead</b>	approx. 19.6 kg
<b>fastening</b>	approx. 3,0 m; mains plug
<b>decorative contrast side parts</b>	US-ConnectionStandard
<b>special features</b>	floor standing base
	metallic silver
	luminaire head detachable, Direct light component with edge light and light-guide technology for homogenous light exit, integrated light and presence sensor PIR, retrofittable with TALK module, separated; direct and indirect light individually adjustable



CEE 7/VI

**luminous intensity**

