

# PRODUCT DATASHEET DP HOUSING 600 2x Lamp IP65

DAMP PROOF HOUSING | Damp-proof luminaire for T8 LED lamps



## **Product benefits**

- Prewired for easy installation of tubular AC LED lamps
- Robust housing
- Easy and quick installation
- 5 years guarantee

## **Product features**

- Luminaire housing, available for 1 or 2 T8 LED lamps
- Type of protection: IP65
- Suitable for SubstiTUBE EM/UN and SubstiTUBE Connected



## **TECHNICAL DATA**

## Electrical data


Nominal voltage	220240 V
Mains frequency	5060 Hz
Max. no. of lum. on circuit break. B16 A	-
Max. no. of lum. on circuit break. C16 A	-
Protection class	1

### Photometrical data

Flickering metric (Pst LM)	-
Stroboscope effect metric (SVM)	-
Beam angle	105 °

# **Dimensions & Weight**

Length	651.00 mm
Width	103.00 mm
Height	75.00 mm
Product weight	850.00 g



## Materials & Colors

Product color	Grey	
Housing color	Gray	
Body material	Polycarbonate (PC)	
Cover material	Polycarbonate (PC)	
Light emitting surface material	Polycarbonate (PC)	
Glow Wire Test according to IEC 60695-2-12	650 °C	
Mercury content	0.0 mg	

# **Application & Mounting**

Ambient temperature range -30+40 °C		-30+40 °C
-------------------------------------	--	-----------



Temperature range at storage -2080 °C	
Type of connection	Screw terminal
Type of protection	IP65
Protection class IK (shock resistance)	IK08
Dimmable	No
Mounting type	Surface
Mounting location	Ceiling
Application environment	Indoor
With light source	No

### Certificates & Standards

Standards	CE / TÜV Rheinland / EAC / RoHS	
Luminaire with limited surface temperature, "D sign"	No	
Ball shot safe	No	

## **EQUIPMENT / ACCESSORIES**

- All required accessories included

## **DOWNLOAD DATA**

	DOWNLOAD DATA
PDF	User instruction
	Tender documents
PDF	Declarations of conformity

## **LOGISTICAL DATA**

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075312425	Shipping box 6	670 mm x 231 mm x 245 mm	6794.00 g	37.92 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

# References / Links



- For Guarantee see www.ledvance.com/guarantee

## **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

