



Circular Connectors IP68  
Circular Connectors AC 173 click

## AC 173 RBUP/5

socket, connection type: screwless, 5 pole, voltage rating: 500 V, current rating: 17.5 A



### Order Info

reference number (ref.no.)	26017
PU	200
EAN	4028012174256

### Type

type	socket
number of poles	5 pole
clamping units per pole	1
colour	black
connection type	screwless
protection against incorrect plugging	yes

### Technical Data

voltage rating	500 V
current rating	17.5 A
impulse voltage rating	2.5 kV
insulating material	PA 6.6
core cross-section min.	0.25 mm <sup>2</sup>
core cross-section max.	1.5 mm <sup>2</sup>
flammability rating	V-0
max. ambient temperature operation	60 °C
IP code	IP66/IP68/IP69
stripping length	12.0 mm
dismantling length	25.0 mm
assembly strain relief	⌚ 2.5 Nm
cable diameter min.	7.0 mm
cable diameter max.	13.0 mm

### Approvals

acc. to EN 61984

[Download PDF](#)

## Accessories

<b>AC 173 BC SW</b>	26280
<b>AC 169 WKZ SW21/24</b>	749960
<b>AC 173 RWZ/5</b>	26060
<b>AC 173 RVKB</b>	26032
<b>DR 16 RH</b>	729011
<b>DR 16 GS</b>	729032
<b>DR 16 1x14,0</b>	729031
<b>DR 16 1x4,0</b>	729033
<b>DR 16 1x6,5</b>	729034
<b>DR 16 2x4,0</b>	729035
<b>DR 16 2x5,5</b>	729036
<b>DR 16 3x4,0</b>	729037
<b>DR 16 4x3,5</b>	729038
<b>DR 16 5x3,5</b>	729009