


TUBIC LED wall surface mounted luminaire TUBIC

Artikel-Nr. 10042173

Licht.
Für Generationen.**Tender**

LED wall surface mounted luminaire TUBIC, white, round. Surface mounting, Wall-mounted. LED wall surface mounted light with up & down light emission 2 x 4.75 W / 2 x 420 lm and 1.5 W / 130 lm indirect light component. Mounting method: Surface mounting, Place of installation: Wall-mounted, Material: Aluminium / Glass / Plastic, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) I, Voltage: 230V AC 50Hz, Power: 10.5W, Amount of light sources / fittings: 2.0 Qty, Luminous flux: 970lm, Colour temperature: 3.000 K, Light colour : White, Beam angle: 40°, With control gear: Yes, Control: on/off.

Article data	
Artikel-Nr.	10042173
GTIN	4251433915737
Series name	TUBIC
Kurzbeschreibung	LED wall surface mounted luminaire TUBIC
Material	Aluminium / Plastic
Colour	White
Type of surface	Matt
Shape	round
Outer diameter	100 mm
Aufbauhöhe	126 mm
scope of delivery	Incl. converter for connection to the 230-V mains voltage
weight	1.512 kg

TUBIC LED wall surface mounted luminaire TUBIC

Artikel-Nr. 10042173

Licht.
Für Generationen.

Lighting technology	
Colour temperature	3000 K
Light colour	White
Light output	Direct/Indirect
Luminous flux	970 lm
System efficiency	92 lm/W
Colour rendering	CRI > 90
Reflector	High-gloss
Beam angle	40 °
Light sharing	Symmetric

Operating technology of the luminaires	
System output	10.5 W
Voltage type	AC
AC nominal voltage max	230 V
Frequenz max.	50 Hz
Lamp	LED
Protection class	I
Degree of protection	IP20
Control	on/off
Leuchtmittelwechsel möglich	ja

Mounting technology	
Mounting method	Surface mounting
Place of installation	Wall-mounted
Adjustability	Not adjustable
Material cover	Plastic, transparent

Packing data	
Gross weight	1.628 kg
Length of packaging	130 mm
Packaging width	130 mm
Packaging height	200 mm