



Circular Plug Connectors IP68
Circular Plug Connectors AC 167 micro
AC 167 RST/ 2



Plug, 2 pole, Voltage Rating: 250 V, Current Rating: 10.0 A

Order Info

Reference Number (ref. no.)	72206216
Applications	Lighting, Installation
PU	200
EAN	4028012125999

Type

Type	Plug
Number of poles	2 pole
Clamping Units per Pole	1
Colour	black
Connection Type	Screw
Protection Against Incorrect Plugging	yes
Latch	yes

Technical Data

Voltage Rating	250 V
Current Rating	10.0 A
Insulating Material	PA 6.6
Contact Material	Brass
Core Cross-Section min.	0.25 mm ²
Core Cross-Section max.	1.0 mm ²
Flammability Rating	V-2
max. Ambient Temperature Operation	85 °C
IP Code	IP68
Type of Conductor Solid	yes
Type of Conductor Flexible	yes
Type of Conductor Stranded	yes
Stripping Length	6.0 mm
Assembly Contact Screw	0.5x3.0 / \cup 2.0 Nm
Assembly Strain Relief	\cup 2.5 Nm
Cable Diameter min.	5.8 mm
Cable Diameter max.	6.9 mm

Accessories

AC 167 WKZ	729041
AC 169 BC black	729030
AC 167 RVKB M16	729043
AC 167 RVKS M16	729042