



83-A1043-0006



series: GLADIATOR SL I Accu Workplace luminaires

Type of installation: portable
 Type of Protection: IP 66
 Protection Class: III
 Lamp: LED
 Dimensions: L 283, B 272, H 104
 Colour: black

Gehäuse Kunststoff anthrazit/blau (Polycarbonat, Kantenschutz mit weichem, thermoplastischen Elastomer - TPE), Abdeckung Kunststoff opal (Polycarbonat), Griff Kunststoff schwarz (ABS), 5-stufig schaltbar, mit Kapazitäts- und Laufzeitanzeige, inkl. Steckernetzteil mit 5 m Zuleitung H05RN-F

electro-technics:

Electric Gear Converter
 System Capacity 24 W
 Voltage 220 - 240 V / 50 - 60 Hz

Spezifikationen:

Colour TPE blue
 Colour handle black
 Power supply cable H05RN-F
 Size power supply cable 2 x 1,0 mm²
 Length power supply cable 5 m
 Colour power supply cable black
 Additional functions with switch
 Lamp cover opal

testings:

Type of Protection IP 66
 Protection Class III
 Glow Wire Test 850°C - 30 seconds
 Impact Protection IK07 (2 Joule)
 Safety Marks D-mark
 Other Marks WEEE mark
 Country Code CE
 Energy efficiency class LED A++
 Energy efficiency class of included lamp A++

lamp 1:

Lamp LED
 Number of Lamps 1
 Wattage 26,00 W
 Socket without socket
 Colour Temperature 5000 K
 Colour rendering index (CRI) 1 80
 Lifespan

weights and measures:

Length L 283 mm
 Width B 272 mm
 Height H 104 mm
 Weight 2,4 kg

lighting technology:

Luminaire flux 3.500 lm

accessories

95-0290-0006 Transport bag for work light blue
 95-0170-0001 Tripod Standard, without castors, set with mounting rail for 1 work light verzinkt
 95-0171-0001 Tripod Standard, with castors, set with mounting rail for 1 work light verzinkt
 95-0172-0001 Tripod Standard, without castors, set with mounting rail for 2 work lights verzinkt
 95-0173-0001 Tripod Standard, with castors, set with mounting rail for 2 work lights verzinkt
 95-0270-0001 Magnet set, for attachment to the threaded bushes in the handle black