



Circular Plug Connectors IP68 Circular Plug Connectors AC 169 kompakt

AC 169 RST/ 4-3

Plug, 3 pole, Voltage Rating: 450 V, Current Rating: 17.5 A, Cross-Section: 1.5 mm²

Order Info

Reference Number (ref. no.)	72201453
Applications	Lighting, Installation
PU	200
EAN	4028012131884

Type

Type	Plug
Number of poles	3 pole
Clamping Units per Pole	1
Colour	black
Cross-Section	1.5 mm ²
Connection Type	Screw
PE Function	yes
Protection Against Incorrect Plugging	yes

Technical Data

Voltage Rating	450 V
Current Rating	17.5 A
Insulating Material	PA 6.6
Contact Material	Brass
Core Cross-Section min.	0.75 mm ²
Core Cross-Section max.	2.5 mm ²
Impulse Voltage Rating	4.0 kV
Flammability Rating	V-2
max. Ambient Temperature Operation	85 °C
IP Code	IP68
Type of Conductor Solid	yes
Type of Conductor Flexible	yes
Type of Conductor Stranded	yes
Stripping Length	6.0 mm
Assembly Contact Screw	0.5x3.0 / ⌀ 0.5 Nm
Assembly Strain Relief	⌀ 2.5 Nm
Cable Diameter min.	7.0 mm

Cable Diameter max. 13.5 mm

Accessories

AC 169 RVKB M25	729164
AC 169 RVKB M20	729184
AC 169 RVKS/ M25	729260
AC 169 RVKS M20	729280
AC 169 WKZ SW21/24	749960
AC 169 WKZ SW21/24	749960
DR 16 5x3,5	729009
DR 16 RH	729011
DR 16 1x13,0	729031
DR GS 16 closed	729032
DR 16 1x2,5	729033
DR 16 1x5,0	729034
DR 16 2x2,5	729035
DR 16 2x4,5	729036
DR 16 3x2,5	729037
DR 16 4x2,5	729038
DR 16 5x3,5	729009
DR 16 RH	729011
DR 16 1x13,0	729031
DR GS 16 closed	729032
DR 16 1x2,5	729033
DR 16 1x5,0	729034
DR 16 2x2,5	729035
DR 16 2x4,5	729036
DR 16 3x2,5	729037
DR 16 4x2,5	729038
DR GS 16 closed	729032
DR 16 1x2,5	729033
DR 16 1x5,0	729034
DR 16 2x2,5	729035
DR 16 2x4,5	729036
DR 16 3x2,5	729037
DR 16 4x2,5	729038
DR 16 RH	729011
DR 16 5x3,5	729009
DR 16 1x13,0	729031
LCS 75/ 3-2	526232