
Motion detector IS 240 DUO

white EAN 4007841 602819 Article number 602819







Function description

Round the corner. Infrared wall sensor IS 240 DUO, for indoors and out, 240° angle of coverage, reach up to 12 m, selectable time and twilight threshold, detection zone can be customised with shrouds.

white EAN 4007841 602819 Article number 602819



Technical specifications

Туре	Motion detectors
Dimensions (L x W x H)	100 x 60 x 90 mm
Mains power supply	230 – 240 V / 50 Hz
Sensor Technology	passive infrared
Application, place	Indoors, Outdoors
Installation site	wall, corner
Installation	Surface wiring
Mounting height	1,80 – 4,00 m
Reach, radial	r = 5 m (52 m ²)
Reach, tangential	r = 12 m (302 m ²)
Detection angle	240 °
Angle of aperture	180 °
Switching zones	276 switching zones
Optimum mounting height	2 m
Mechanical scalability	No
Sneak-by guard	Yes
Capability of masking out individual segments	Yes
Electronic scalability	No
Twilight setting TEACH	No
Twilight setting	2 – 2000 lx
Time setting	10 s – 15 Min.
Output	1000 W
Switching output 1, resistive	1000 W
Switching output 1, number of LEDs / _{6 pcs.} fluorescent lamps	

	500.1/4
Fluorescent lamps, uncorrected	500 VA
Fluorescent lamps, series-corrected	500 VA
Fluorescent lamps, parallel-corrected	5000 VA
Switching output 1, low-voltage halogen lamps	1000 VA
LED lamps	16 W
LED lamps > 2 W	64 W
LED lamps > 8 W	64 W
Capacitive load in µF	132 μF
Constant-lighting control	No
Basic light level function	No
Settings via	Potentiometers
With remote control	No
Interconnection	Yes
Type of interconnection	Master/master
IP-rating	IP54
Material	Plastic
Ambient temperature	-20 – 50 °C
Application, room	outdoors, front door, all round the building, terrace / balcony, courtyarc & driveway
Colour	white
Colour, RAL	9010
Manufacturer's Warranty	3 years
Version	white
	4007841602819

Accessories

EAN 4007841 630218


Corner wall mount 01

Motion detector IS 240 DUO

white EAN 4007841 602819 Article number 602819




Detection Zone




Mögliche Montagehöhe: 1,80 m – 4,00 m Orange: radial Schwarz: tangential


Light without neutral conductor




Connection using two-circuit switch for manual and automatic operation



Dimension Drawing



Light with neutral conductor



Connection via a two-way switch for manual override and automatic operation

