

DALI Sensor Coupler E

DALI Sensor Coupler E | Sensors for light management systems



Areas of application

- Connection of light and presence sensors in DALI systems
- Ceiling or independent installation via ECO CI KIT possible
- Suitable for external light and presence sensors
- Installation in industry and office luminaires
- Corridors
- Warehouses

Product benefits

- Small housing design

Product features

- Suitable for daylight-dependent control


Product datasheet

Technical data

Electrical data

System wattage	0.30 W
Nominal voltage	230 V
Mains frequency	50 Hz

Dimensions & weight



Length	118.0 mm
Width	30.0 mm
Height	21.0 mm
Mounting hole spacing, length	110.0 mm
Product weight	50.00 g

Temperatures & operating conditions

Ambient temperature range	-20...+50 °C
---------------------------	--------------

Capabilities

Dimming interface	DALI
Number of control outputs	1
Type of installation	Luminaire integration/Ceiling integration

Certificates & standards


Type of protection	IP20
--------------------	------

Equipment / Accessories

- Separate installation possible with ECO CI KIT
- Suitable for many OSRAM DALI control systems

Product datasheet

Download Data

File	
	Installation guide 612042_Technical Instruction DALI Sensor Coupler E

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899230491	DALI Sensor Coupler E	Shipping carton box 25	200 mm x 140 mm x 147 mm	4.12 dm ³	1670.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.