



2330 LED

LED recessed luminaire

- Flexible luminous intensity
- VDU workstation-compliant
- Energy-efficient

2330 LED is a recessed luminaire for system ceilings in 600 x 600 mm grid size. It scores points with pleasantly uniform light distribution and with UGR < 19 is suitable for VDU workstations. Thanks to multi-lumen technology, the luminaire luminous flux can be adapted to conditions on location. Typical applications are offices, corridors, foyers, conference rooms, sales areas and waiting zones. This will get the job done!

Why you'll master the job with the 2330 LED recessed luminaire

- Flexible modification of luminaire luminous flux (3,600 lm, 2,900 lm) thanks to multi-lumen technology.
- Pleasant light effect due to uniform illumination, suitable for VDU workstations (UGR < 19).
- Separate control gear unit simplifies installation (and replacement).
- 1:1 replacement of conventional luminaires offering time and cost savings during refurbishment.
- Can be covered with insulation material
- High efficiency (up to 116 lm/W) and reliable service life (50,000 h, L65)
- Additional installation possibilities with suspension accessories (available separately)

2330 LED at a glance

Dimensions (L x B x H):	595 x 595 x 34 mm
Luminaire luminous flux::	3,600 lm, 2,900 lm
Colour rendering/-temperature:	Ra > 80 / 3000, 4000 K
Connected load:	31 W, 24 W
Protection rating, safety class:	IP20/IK02, I
Weight:	2.2 kg

All versions of 2330 LED

Product reference	TOC	Luminous flux [lm]	Wattage [W]	Light colour [K]	Dimensions LxBxH [mm]	Replacement
DALI dimmable						
2330 G3 M73 PW19 3600-830 ETDD	7631851	3400	31	3000	595 x 595 x 34	3 x 14 / 4 x 14 W 3 x 18 / 4 x 18 W
2330 G3 M73 PW19 3600-840 ETDD	7631751	3600	31	4000	595 x 595 x 34	3 x 14 / 4 x 14 W 3 x 18 / 4 x 18 W
Multilumen (adjustable luminaire luminous flux)						
2330 G3 M73 PW19 36/29/ML-830 ET	7632040	3400 / 2800	31/24	3000	595 x 595 x 34	3 x 14 / 4 x 14 W 3 x 18 / 4 x 18 W
2330 G3 M73 PW19 36/29/ML-840 ET	7631940	3600 / 2900	31/24	4000	595 x 595 x 34	3 x 14 / 4 x 14 W 3 x 18 / 4 x 18 W

Parts for 2330 LED

Product reference	TOC	Description	Colour	Dimensions L x W x H [mm]	Weight
2330 G3 ZH/M73 M84	7716400	Suspension accessories	Zinc	100 x 80 x 15	0,2 kg