

## Product information 74R WD1 LED1000-830 ET TOC: 6857740



### Luminaire type

Round surface-mounted LED luminaire with opal PMMA diffuser.

### Applications

For entrance areas, corridors, stairways, lounges, hotels, restaurants and residential zones.

### Mounting methods

For wall or ceiling mounting.

### Optical system

With round, spherically-shaped diffuser, slightly flattened on the luminaire head, opal.

### LED system

Luminaire luminous flux 1300 lm, connected load 13 W, luminous efficiency of luminaire 100 lm/W. Light colour warm white, colour temperature 3000 K, colour rendering index  $R_a > 80$ . Service life  $L_{80}(t_q 25^\circ\text{C}) = 50,000$  h.

### Luminaire body


Luminaire body of sheet steel, white, powder-coated. Diameter of diffuser  $\varnothing 320$  mm.

### Electrical version

With electronic transformer, switchable.

### Specification text

Round surface-mounted LED luminaire with opal PMMA diffuser. For wall or ceiling mounting. With round, spherically-shaped diffuser, slightly flattened on the luminaire head, opal. Luminaire luminous flux 1300 lm, connected load 13 W, luminous efficiency of luminaire 100 lm/W. Light colour warm white, colour temperature 3000 K, colour rendering index  $R_a > 80$ . Service life  $L_{80}(t_q 25^\circ\text{C}) = 50,000$  h. Luminaire body of sheet steel, white, powder-coated. Diameter of diffuser  $\varnothing 320$  mm. Safety class I, protection rating IP40, impact resistance IK02/0,2 J, heat resistance  $650^\circ\text{C}$ . With electronic transformer, switchable.



Colour	<b>white ( ...01)</b>
Safety class	<b>I</b>
Hot wire test	<b>650 °C</b>
Impact resistance	<b>0,2 J</b>
Degree of protection	<b>IP40</b>
LFEC	<b>F0</b>
Cibse	<b>BZ 5</b>
LOR	<b>1,00</b>

