Sensor-switched outdoor light

L 800 S

V2 Anthracite EAN 4007841 035747 Article number 035747









3000 K















Downlight L 825

30 years (Ø 4,5h /

w

inte frequ

intelligent high frequency senso

:

II

2 - 1000 lux

: - 15 min soft lig

Manual overrid

Function description

The most modern outdoor light in the world. Designer sensor-switched outdoor light L 800 S with invisible high-frequency sensor, ideal for building entrances and fronts of buildings, 7,5 W STEINEL LED lighting system, 466 lm, 160° coverage angle, reach from 1 - 5 m, for stylish downlighting, includes soft light start and optional manual override for 4 hours.

Sensor-switched outdoor light

L 800 S

V2 Anthracite EAN 4007841 035747 Article number 035747



Technical specifications

Dimensions (L x W x H)	230 x 145 x 88 mm
Mains power supply	220 – 240 V / 50 – 60 Hz
Sensor Technology	iHF (intelligent high-frequency technology)
Transmitter power	
Output	7,5 W
Interconnection	No
Slave modeselectable	Yes
Lichtstrom Gesamtprodukt	466 lm
Gesamtprodukt Effizienz	62 lm/W
Colour temperature	3000 K
With lamp	Yes, LED lamp
Lamp	LED cannot be replaced
LED life expectancy (25 °C)	> 60000 h
Base	without
LED cooling system	Active and Passive Thermo Control
With motion detector	Yes
Detection angle	160 °
Capability of masking out individual segments	No
Electronic scalability	Yes
Mechanical scalability	No
Reach, radial	$r = 5 \text{ m} (35 \text{ m}^2)$

Reach, tangential	$r = 5 \text{ m} (35 \text{ m}^2)$
Continuous light	selectable, 4h
Photo-cell controller	Yes
Twilight setting	2 – 2000 lx
Time setting	5 s - 15 Min.
Basic light level function	Yes
Basic light level function time	10/30 min, all night
Functions	Motions sensor
Soft light start	Yes
Impact resistance	IK03
IP-rating	IP44
Protection class	II
Ambient temperature	-20 - 40 °C
Housing material	Aluminium
Cover material	Plastic, opal
Manufacturer's Warranty	3 years
Settings via	Potentiometers
With remote control	No
Installation site	wall
Version	Anthracite
PU1, EAN	4007841035747

Dimension Drawing

230 — 146 —

Circuit diagram

