Motion detector - Professional Line

iHF 3D

COM1 - black EAN 4007841 066215 Article number 066215









2000 W













Teach

intelligent high frequency sensor 160°

3 zones scalable 3 x 1-7m, max. 7 m

2000 W max. (LED-ready)

5 sec - 60 min (via App)

Teach mode

Function description

Makes all the difference outside. Precisely where you want it to. iHF 3D motion detector, ideal for facades, carports, parking areas and patios. 160° iHF-sensor with 7 m reach, 3D aerial technology, identifies and distinguishes between moving objects, no inadvertent triggering any more by small animals, very low or high temperatures. Detects everything equally well whichever direction it is approached from. Easy to adjust and interconnect by app and Bluetooth.

Technical specifications

Motion detectors
120 x 117 x 120 mm
220 – 240 V / 50 – 60 Hz
iHF (intelligent high-frequency technology)
Outdoors
wall
Surface wiring
1,80 – 2,00 m
r = 7 m (68 m ²)
r = 7 m (68 m ²)
Detection zone adjustable on 3 axes
5,8 GHz
160 °
100 °
1,8 m
No
Yes
Yes
Yes

Twilight setting TEACH	Yes
Twilight setting	2 – 2000 lx
Time setting	5 s – 60 Min.
Switching output 1, resistive	2000 W
Constant-lighting control	No
Basic light level function	No
Functions	Normal / test mode, Manual ON / ON-OFF
Settings via	Potentiometers, Bluetooth
Interconnection	Yes
Type of interconnection	Master/master
IP-rating	IP54
Material	Plastic
Ambient temperature	-20 – 50 °C
Application, room	outdoors, front door, all round the building, terrace / balcony, courtyard & driveway
Colour	black
Colour, RAL	9005
Manufacturer's Warranty	5 years
Version	COM1 - black
PU1, EAN	4007841066215


Motion detector - Professional Line

iHF 3D

COM1 - black EAN 4007841 066215 Article number 066215




Detection Zone



Mögliche Montagehöhe: 1,80 m – 2,00 m Orange: radial und tangential 3 skallerbare Achsen

Master circuit diagram



Dimension Drawing

