

CERTIFICATE ENEC/FI 2014011



Our Ref. 273106-1

Product Electronic ballast for tubular fluorescent lamps
Rating and principal characteristics See pages 2-3
Trade mark (if any) HELVAR
Type EL1x54sc, EL1x24sc, EL1x39sc, EL1x49sc, EL1x80sc, EL4x14sc, EL1x55sc, EL2x55sc, EL1x36sc, EL2x36sc, EL1x58sc, EL1x70sc, EL1x18sc, EL2x18sc, EL2x58sc, EL4x18sc, EL1x21sc, EL1x14sc, EL1x28sc, EL1x35sc, EL2x14sc, EL2x21sc, EL2x24sc, EL2x28sc, EL2x35sc, EL2x39sc, EL2x49sc, EL2x54sc

Name and address of the licensee Helvar Oy Ab, PL 100, FI-03601 KARKKILA, FINLAND

Address of the manufacturer Helvar Oy Ab, Yrittäjätie 23, FI- 03600 KARKKILA, FINLAND

Is in conformity with EN 61347-2-3:2011
 EN 61347-1:2008 + A1:2011 + A2:2013
 EN 60929:2011
 IEC 61347-2-3:2011 (Ed 2)
 IEC 61347-1:2007 (Ed 2) + A1:2010 + A2:2012
 IEC 60929:2011 (Ed 4)

As shown in the Test Report(s) No(s) 258282-3_A, 258282-3_B, 258282-2_A, 258282-2_B, 248578-1c, 248578-1d, 258282-1_A, 258282-1_B, 258282-3_A Amendment-1, 221483-1...4, 221483-6...9, 268862-1_A, 268862-1_B, 273106-1A...F

It is authorized to use of the marks ENEC 16 and FI

Validity This certificate is valid until 26 February 2019 unless the standard in question has been amended or superseded with significant changes in requirements, in which case, SGS Fimko has the right to shorten the validity of the certificate based on the legislation of the European Union. This certificate includes the right to use the ENEC 16 and FI mark under the condition that changes (if any) will be checked at SGS Fimko before the product is brought onto market and that the conditions for ENEC and FI certification are met.

Directive information The product(s) fulfils the essential safety requirements for CE conformity marking according to the Low Voltage Directive (2006/95/EC) at the date of issue of this certificate.

With the following limitations -

Date of issue 26 February 2014

SGS Fimko Ltd

Signature

Pasi Orreveteläinen
 Team Leader



This certificate has 2 pages



This certificate is issued by the company under its General Conditions for Certification Services accessible at <http://www.sgs.fi/en/Terms-and-Conditions.aspx>. Attention is drawn to the limitations of liability defined therein and in the Test Report here above mentioned which findings are reflected in this certificate. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Rating and principal characteristics

EL4x14sc, EL4x18sc:

4xFDH-14W-G5 (T5); 220-240V, 50-60Hz; 0,29-0,27A; Tc 80°C; λ 0,98;
U-out 400V

4xFD-18W-G13 (T8); 220-240V, 50-60Hz; 0,33-0,30A; Tc 80°C; λ 0,98;
U-out 350V

EL2x55sc, EL2x36sc, EL2x18sc, EL2x58sc, EL2x14sc, EL2x21sc, EL2x24sc,
EL2x28sc, EL2x35sc, EL2x39sc, EL2x49sc, EL2x54sc:

2xFDH-14W-G5 (T5); 220-240V, 50-60Hz ; 0,15-0,14A ; Tc 80°C; λ 0,98;
U-out 250V

2xFD-18W-G13 (T8); 220-240V, 50-60Hz ; 0,18-0,15A ; Tc 80°C; λ 0,98;
U-out 250V

2xFDH-21W-G5 (T5); 220-240V, 50-60Hz ; 0,22-0,20A ; Tc 80°C; λ 0,98;
U-out 250V

2xFDH-24W-G5 (T5); 220-240V, 50-60Hz ; 0,24-0,20A ; Tc 80°C; λ 0,98;
U-out 400V

2xFDH-28W-G5 (T5); 220-240V, 50-60Hz ; 0,30-0,28A ; Tc 80°C; λ 0,98;
U-out 350V

2xFDH-35W-G5 (T5); 220-240V, 50-60Hz ; 0,36-0,34A ; Tc 80°C; λ 0,98;
U-out 350V

2xFD-36W-G13 (T8) / 2xFSD-36W-2G11 (TC-L); 220-240V, 50-60Hz ;
0,33-0,30A ; Tc 80°C; λ 0,98 ; U-out 250V

2xFDH-39W-G5 (T5); 220-240V, 50-60Hz ; 0,40-0,36A ; Tc 80°C; λ 0,98;
U-out 400V

2xFDH-49W-G5 (T5); 220-240V, 50-60Hz ; 0,50-0,46A ; Tc 80°C; λ 0,98;
U-out 400V

2xFDH-54W-G5 (T5); 220-240V, 50-60Hz ; 0,53-0,49A ; Tc 80°C; λ 0,98;
U-out 400V

2xFD-55W-2G11 (TC-L); 220-240V, 50-60Hz ; 0,53-0,49A ; Tc 80°C; λ 0,98;
U-out 350V

2xFD-58W-G13 (T8) ; 220-240V, 50-60Hz ; 0,50-0,46A ; Tc 80°C ; λ 0,98;
U-out 400V

EL1x14sc, EL1x18sc, EL1x21sc, EL1x28sc, EL1x35sc, EL1x36sc, EL1x55sc,
EL1x58sc, EL1x70sc, EL1x24sc, EL1x39sc, EL1x49sc, EL1x54sc, EL1x80sc:

1xFDH-14W-G5 (T5); 220-240V, 50-60Hz ; 0,08-0,07A ; Tc 80°C; λ 0,98;
U-out 250V

1xFD-18W-G13 (T8); 220-240V, 50-60Hz ; 0,09-0,08A ; Tc 70°C; λ 0,98;
U-out 250V

1xFDH-21W-G5 (T5); 220-240V, 50-60Hz ; 0,11-0,10A ; Tc 80°C; λ 0,98;
U-out 250V

1xFDH-28W-G5 (T5); 220-240V, 50-60Hz ; 0,15-0,14A ; Tc 80°C; λ 0,98;
U-out 350V

1xFDH-35W-G5 (T5); 220-240V, 50-60Hz ; 0,18-0,17A ; Tc 80°C; λ 0,98;
U-out 350V

1xFD-36W-G13 (T8) / 1xFSD-36W-2G11 (TC-L); 220-240V, 50-60Hz ;
0,17-0,16A ; Tc 80°C; λ 0,98; U-out 250V

1xFSDH-55W-2G11 (TC-L); 220-240V, 50-60Hz ; 0,28-0,26A ; Tc 80°C;
λ 0,98; U-out 350V

1xFD-58W-G13 (T8) ; 220-240V, 50-60Hz ; 0,27-0,26A ; Tc 80°C ; λ 0,98;
U-out 400V

1xFD-70W-G13 (T8) ; 220-240V, 50-60Hz ; 0,31-0,27A ; Tc 70°C ; λ 0,98;
U-out 400V

1xFDH-24W-G5 (T5); 220-240V, 50-60Hz ; 0,13-0,12A ; Tc 80°C; λ 0,98;
U-out 400V

1xFDH-39W-G5 (T5); 220-240V, 50-60Hz ; 0,20-0,18A ; Tc 80°C; λ 0,98;
U-out 400V

1xFDH-49W-G5 (T5); 220-240V, 50-60Hz ; 0,25-0,23A ; Tc 80°C; λ 0,98;
U-out 400V

1xFDH-54W-G5 (T5); 220-240V, 50-60Hz ; 0,28-0,26A ; Tc 80°C; λ 0,98;
U-out 400V

1xFDH-80W-G5 (T5); 220-240V, 50-60Hz; 0,41-0,38A; Tc 80°C; λ 0,98;
U-out 400V