

Components for luminaires Catalogue



INDEX

2	Zalux
4	Luminaires Kit Including housing, diffuser, gear tray and accessories
6	DUNA
8	ACQUA
10	ALHAMA
12	PE
14	Single Parts Individual components
16	ACQUA / ALHAMA / DUNA
18	PE
19	Accessories
20	Technical information
20	Resistance to chemical agents
21	Ingress and impact protection
22	General sale conditions







ZALUX is the European OEM leader for weatherproof luminaires and components.

Specialised in the OEM development and manufacturing of reliable and durable luminaires for extreme conditions such as a wide range of temperatures, dust, humidity and chemicals.



Efficient and quality luminaires specific for different industrial applications, with a wide range of options.



OEM design, engineering and manufacturing of bespoke lighting products to meet special needs.



Explosion proof LED luminaires certified for use in EX-Zones according to ATEX directive.



- Headquarters in Zaragoza, Spain
- 3 manufacturing plants in Alhama de Aragón
- Quality Made in Spain



ALHAMA I

- Plastic injection
- Compression press
- Extrusion



ALHAMA II

- Metal workshop
- Automated wiring robots
- 20 assembly lines for LED
- Electronic components assembling



ALHAMA III

- New assembling area
- 1500m² premises
- 13 production lines



LABORATORY

- Thermal and endurance tests
- IPX5 X6 humidity tests
- Impact tests
- Product safety tests



WAREHOUSE

- 10,000m² storage
- For 5,800 Europallets
- With advanced computer systems





Luminaires kit









Usual applications:



Characteristics

Housing	Compressed fibreglass reinforced polyester (GRP), or injected polycarbonate (PC) Grey RAL 7035							
Gasket	Polyurethane							
Gear tray	White lacquered steel plate for LED modules							
Gear tray holders	Wide version, to fix the gear tray to the housing and to suspend the gear tray to facilitate connection							
Diffuser	Injected UV protected opal diffuser, with frosted finish to achieve a uniform and optimised light distribution, specific for LED							
	C: impact resistance IK08 1,2 and 1.5 versions only Complete range							
	PMMA: high chemical resistance IK03 and better transmittance							

Accesory bag

Closing clips	Plastic (polyamide) or stainless steel (INOX)
Fixing clips, suspension triangles	Stainless steel
Cable entry	Grommet



Accessory bag with plastic clips


Dimensions and logistics

Ix 0.6 660 390 101 84 101 675 x 105 x 80 1 1.02 294 168 + 1 x 1.2 1279 800 101 84 101 1290 x 105 x 80 1 2.03 147 84 + 1 x 1.5 1573 1100 101 84 101 1590 x 105 x 80 1 2.49 147 84 +					KG			Z ALHAMA	Z DUNA	Y	Xm	х	
1 x 1.2 1279 800 101 84 101 1290 x 105 x 80 1 2.03 147 84 + 1 x 1.5 1573 1100 101 84 101 1590 x 105 x 80 1 2.49 147 84 +		Groupage/full truc Pcs./double palle			Box	ts/Box		mm	mm	mm	mm	mm	
1 x 1.5 1573 1100 101 84 101 1590 x 105 x 80 1 2.49 147 84 +	68	168 +168	168	294	1.02	1	675 x 105 x 80	101	84	101	390	660	1 x 0.6
	34	84 + 84	84 -	147	2.03	1	1290 x 105 x 80	101	84	101	800	1279	1 x 1.2
2 x 0.6 660 390 145 84 101 675 x 150 x 80 1 1.28 210 120+	34	84 + 84	84 -	147	2.49	1	1590 x 105 x 80	101	84	101	1100	1573	1 x 1.5
	20	120 + 120	120-	210	1.28	1	675 x 150 x 80	101	84	145	390	660	2 x 0.6
2 x 1.2 1279 800 145 84 101 1290 x 150 x 80 1 2.57 105 60 +	60	60 + 60	60 -	105	2.57	1	1290 x 150 x 80	101	84	145	800	1279	2 x 1.2
2 x 1.5 1573 1100 145 84 101 1590 x 150 x 80 1 3.13 105 60 +	60	60 + 60	60 -	105	3.13	1	1590 x 150 x 80	101	84	145	1100	1573	2 x 1.5

For logistic estimations please contact our sales backoffice team

DUNA DIFFUSER


ALHAMA DIFFUSER





KIT are presented in an individual box comprising:

- Housing
- Gear tray
- Gear tray holders
- Diffuser
- Accesory bag



Order numbers

DUNA PC

PC housing + DUNA PC diffuser

	Plastic closing clips					
	Removable	Unremovable				
1 x 1.2	10210340	10174387				
1 x 1.5	10174392	10174391				

PC housing + ALHAMA PC diffuser

	Plastic closing clips					
	Removable	Unremovable				
1 x 0.6	10174396	10174395				
1 x 1.2	10174400	10174399				
1 x 1.5	10174404	10174403				
2 x 0.6	10174408	10174407				
2 x 1.2	10174412	10174411				
2 x 1.5	10174416	10174415				

Please consult our Sales Team for any other combination

DUNA GRP

GRP housing + DUNA PMMA diffuser

	INOX closing clips					
	Removable	Unremovable				
1 x 1.2	10174390	10174389				
1 x 1.5	10174394	10174393				

GRP housing + ALHAMA PMMA diffuser

	INOX closing clips						
	Removable	Unremovable					
1 x 0.6	10174398	10174397					
1 x 1.2	10174402	10174401					
1 x 1.5	10174406	10174405					
2 x 0.6	10174410	10174409					
2 x 1.2	10174414	10174413					
2 x 1.5	10174418	10174417					

DUNA





Usual applications:



Characteristics

Housing	Compressed fibreglass reinforced polyester (GRP) Grey RAL 7035
Gasket	High quality bi-component polyurethane for extreme durability
Gear tray	White lacquered steel plate for T5 and T8
Gear tray holders	Wide version, to fix the gear tray to the housing and to suspend the gear tray to facilitate connection
Diffuser	Injected UV protected transparent diffuser with prismatic design for an optimum light distribution
	PC: impact resistance IK08
	PMMA: high chemical resistance IK03 and better transmittance

Accesory bag

Closing clips	Plastic (polyamide) or stainless steel (INOX)		~ 1
Fixing clips, suspension triangles	Stainless steel		
Cable entry	Grommet	- In the	

Accessory bag with INOX clips

Accessory bag with plastic clips

Dimensions and logistics

	х	Xm	Y	Z		4	KG		
	mm	mm	mm	mm	L x W x H mm	Kits/Box	Box	Groupage Pcs./pallet	Groupage/full truck Pcs./double pallet
1 x 0.6	662	390	101	101	675 x 105 x 80	1	1.02	294	168 +168
1 x 1.2	1283	800	101	101	1290 x 105 x 80	1	2.03	147	84 + 84
1 x 1.5	1573	1100	101	101	1590 x 105 x 80	1	2.49	147	84 + 84
2 x 0.6	662	390	145	101	675 x 150 x 80	1	1.28	210	120 + 120
2 x 1.2	1283	800	145	101	1290 x 150 x 80	1	2.57	105	60 + 60
2 x 1.5	1573	1100	145	101	1590 x 150 x 80	1	3.13	105	60 + 60
		-		Х					
Y	Y		-	Xm					
			Ψ	U	<u> </u>				



KIT are presented in an individual box comprising:

- Housing
- Gear tray
- Gear tray holders
- Diffuser
- Accesory bag

Order numbers

ACQUA PC

GRP housing + PC diffuser

	Plastic clo	INOX closing clips	
	Т8	T5 or T8	Т8
1 x 0.6	10048346	10088279	10048558
1 x 1.2	10048347	10088280	10048559
1 x 1.5	10048348	10088281	10048560
2 x 0.6	10048349	10088347	10048561
2 x 1.2	10048350	10088348	10048562
2 x 1.5	10048351	10088349	10048563

ACQUA PMMA

GRP housing + PMMA diffuser

	Plastic clo	INOX closing clips		
	Т8	T5 or T8	Т8	
1 x 0.6	10048352	10070297	10048564	
1 x 1.2	10048353	10070298	10035612	
1 x 1.5	10048354	10070299	10048565	
2 x 0.6	10048355	10070300	10035613	
2 x 1.2	10048356	10070301	10035611	
2 x 1.5	10048357	10070302	10048566	





Usual applications:



Characteristics

njected polycarbonate (PC)
Brey RAL 7035
ligh quality bi-component polyurethane for extreme durability
Vhite lacquered steel plate for T5 and T8
larrow version, to fix the gear tray to the housing and to suspend the gear tray to acilitate connection
njected UV protected transparent diffuser with prismatic design for an optimum light distribution
C: impact resistance IK08
MMA: high chemical resistance IK03 and better transmittance

Accesory bag

Closing clips	Plastic (polyamide) or stainless steel (INOX)	0	00
Fixing clips, suspension triangles	Stainless steel	=	451-
Cable entry	Grommet		1-11 =

Accessory bag with INOX clips

Accessory bag with plastic clips

Dimensions and logistics

	х	Xm	Y	Z			KG		
	mm	mm	mm	mm	L x W x H mm	Kits/Box	Box	Groupage Pcs./pallet	Groupage/full truck Pcs./double pallet
1 x 0.6	657	390	101	101	670 x 105 x 75	1	0.93	294	168 + 168
1 x 1.2	1279	800	101	101	1280 x 105 x 75	1	1.89	147	84 + 84
1 x 1.5	1573	1100	101	101	1580 x 105 x 75	1	2.26	147	84 + 84
2 x 0.6	657	390	145	101	670 x 155 x 75	1	1.20	210	120 + 120
2 x 1.2	1279	800	145	101	1280 x 155 x 75	1	2.43	105	60 + 60
2 x 1.5	1578	1100	145	101	1580 x 155 x 75	1	2.89	105	60 + 60

X Xm

10



KIT are presented in an individual box comprising:

- Housing
- Gear tray
- Gear tray holders
- Diffuser
- Accesory bag

Order numbers

ALHAMA PC

PC housing + PC diffuser

	Plastic clo	INOX closing clips		
	Т8	T5 or T8	Т8	
1 x 0.6	10020049	10100800	10020051	
1 x 1.2	10019877	10099728	10019879	
1 x 1.5	10019937	10100801	10019939	
2 x 0.6	10020101	10100802	10020103	
2 x 1.2	10017594	10099729	10017595	
2 x 1.5	10019997	10100803	10019999	

ALHAMA PMMA

PC housing + PMMA diffuser

	Plastic clo	INOX closing clips		
	Т8	T5 or T8	Т8	
1 x 0.6	10020052	10100804	10020054	
1 x 1.2	10019880	10100805	10019882	
1 x 1.5	10019940	10100806	10019942	
2 x 0.6	10020104	10100807	10020106	
2 x 1.2	10017599	10100808	10017600	
2 x 1.5	10020000	10100809	10020002	





Usual applications:



Characteristics


Housing	Compressed fibreglass reinforced polyester (GRP) Grey RAL 7035
Gear tray	White lacquered steel plate
Diffuser	Injected UV protected transparent diffuser with prismatic design for an optimum light distribution PC: impact resistance IK07
	PMMA: high chemical resistance IK03 and better transmittance

Accesory bag

Closing clips	Plastic (polyamide) or stainless steel INOX		
Washers	Rubber Flat	2.22	A CAR
Cable entry	Grommet	INOX closing clips	Plastic closing clips

Dimensions and logistics

	х	Xm	Y	Z			KG		
	mm	mm	mm	mm	L x W x H mm	Kits/Box	Box	Groupage Pcs./pallet	Groupage/full truck Pcs./double pallet
1 x 0.6	666	230	100	108	675 x 110 x 95	1	1.02	224	140 + 140
1 x 1.2	1275	840	100	108	1285 x 110 x 95	1	2.03	112	70 + 70
1 x 1.5	1575	1140	100	108	1585 x 110 x 95	1	2.49	112	70 + 70
2 x 0.6	666	230	170	108	675 x 175 x 95	1	1.28	128	80 + 80
2 x 1.2	1275	840	170	108	1285 x 175 x 95	1	2.57	64	40 + 40
2 x 1.5	1575	1140	170	108	1580 x 155 x 75	1	2.89	64	40 + 40





KIT are presented in an individual box comprising:

- Housing
- Gear tray
- Turnbuckle
- Diffuser
- Accesory bag

Order numbers

PEP

GRP housing + PC diffuser

	5				
	Plastic closing clips	INOX closing clips		Plastic closing clips	INOX closing clips
1 x 0.6	10012175	10012177	1 x 0.6	10012491	10015103
1 x 1.2	10012218	10012220	1 x 1.2	10007416	10014666
1 x 1.5	10012274	10015449	1 x 1.5	10012600	10015106
2 x 0.6	10012332	10012334	2 x 0.6	10012651	10015104
2 x 1.2	10007411	10012379	2 x 1.2	10007420	10015105
2 x 1.5	10012438	10015450	2 x 1.5	10012763	10015107

PEM

GRP housing + PMMA diffuser

The products in this catalogue are OEM components requiring final assembly by a qualified OEM manufacturer. Data subject to change. Version	2020.2





Single parts



Zalux 15

ACQUA / ALHAMA / DUNA

Housing

			Order number	Units/Box	KG Box	Box/Pallet	Box/Pallet
		1 x 0.6	10118008	120	29	8	10
11		1 x 1.2 ¹	10118009	125	57	4	5
	ACQUA	1 x 1.5 ¹	10118010	125	71	4	5
1	GRP	2 x 0.6	10118011	75	24	8	10
		2 x 1.2	10118012	70	44	4	5
		2 x 1.5	10118014	70	52	4	5
		1 × 0 6	10000501	120	29	0	10
		1 x 0.6	10099521	120		8	
1. 1		1 x 1.2 ¹	10099542	120	57	4	5
1	ALHAMA	1 x 1.5 ¹	10099543	120	71	4	5
1	PC	2 x 0.6	10099544	75	24	8	10
		2 x 1.2	10099545	75	44	4	5
		2 x 1.5	10099546	75	52	4	5

All housings are compatible with ALHAMA diffusers

¹Also compatible with DUNA diffuser

Diffuser

			Order r	number	Æ	KG		
- A			PC	PMMA	Units/Box	Box	Box/Pallet	Box/Pallet
		1 x 0.6	10020697	10109202	200	45	8	10
1 al		1 x 1.2	10020701	10111261	200	87	4	5
	ALHAMA	1 x 1.5	10020703	10111240	200	104	4	5
	transparent	2 x 0.6	10020699	10111241	130	38	8	10
		2 x 1.2	10017591	10111262	130	71	4	5
		2 x 1.5	10020705	10111242	130	87	4	5
C X								
		1 x 0.6	10124902	10140241	200	45	8	10
		1 x 1.2	10117363	10120962	200	87	4	5
	ALHAMA	1 x 1.5	10124903	10115727	200	104	4	5
	semi opal	2 x 0.6	10125953	10146041	130	38	8	10
		2 x 1.2	10122361	10146042	130	71	4	5
		2 x 1.5	10122364	10146043	130	87	4	5
-	DUNA ²	1 x 1.2	10138722	10138723	240	45	4	5
	opal	1 x 1.5	10138724	10138725	240	87	4	5
	² Slimmer diffuser s	pecially design	ned for high perform	ance of LED lumina	ires			

²Slimmer diffuser specially designed for high performance of LED luminaires

Transparent diffusers are recommended for T5 and T8. Semi opal diffusers are recommended for LED modules. Supplied in bulk packages. For logistic estimations please contact our sales backoffice team.

Gear tray

			Order number LED 32 + 40 mm ZHAGA	Order number LED 24 mm ZHAGA	Units/Box	KG Box	Box/Pallet	Box/Pallet
		1 x 0.6	10140240 1	10165083	460	130	2	2
-		1 x 1.2	10136502 1	10145649 1	460	261	1	1
	LED	1 x 1.5	10136503 1	10145650 1	460	325	1	1
		2-1 x 0.6	10145646 1	10155603	270	101	2	2
		2-1 x 1.2	10145647 1	10145651 ²	270	195	1	1
		2-1 x 1.5	10145648 1	10145652 ²	270	260	1	1

¹ It requires wide gear tray holder. ² It requires narrow gear tray holder.

			Order number T8	Order number T5 or T8 ³	Order number T5	Units/Box	KG Box	Box/Pallet	Box/Pallet
and the second second		1 x 0.6	10020719	10075943	10020717	460	130	2	2
		1 x 1.2	10020723	10075944	10020721	460	261	1	1
	T5 I T8	1 x 1.5	10020727	10075945	10020725	460	325	1	1
	10110	2 x 0.6	10020731	10075946	10020729	270	101	2	2
		2 x 1.2	10017590	10075967	10075971	270	195	1	1
		2 x 1.5	10020735	10075968	10020733	270	260	1	1

³Universal

Gear tray holder⁴

For GRP housing

		Order number
LED	Wide gear tray holder for GRP housir (LED module)	ng 10119008
Т5-Т8	Narrow gear tray holder for GRP housing (T8-T5-LED tube)	10025876
	Wide	Narrow

⁴ Each luminaire requires 2 pieces.

For PC housing

		Order number
LED	Wide gear tray holder set for PC housing (LED module)	Set: 10120146 + 10016244
T5-T8	Narrow gear tray holder for PC housing (T8-T5-LED tube)	Set: 10027074 + 10016244
		<i>i</i>



Wide set

Narrow set

Accessories

For GRP housing

Closing slips		Single		
Closing clips -	0.6	1.2	1.5	clip
Plastic INOX	10025986 10026906	10025987 10026907	10025988 10026908	10025869 10026905





Accessory bag with plastic clips

Accessory bag with INOX clips

For PC housing

Clasing aline		g	Single	
Closing clips	0.6	1.2	1.5	clip
Plastic, removable	10020763	10016237	10020765	10016239
Plastic, unremovable	10125240	10125241	10125242	50123987
INOX, removable	10020764	10016238	10020766	10016245
	2			

Accessory bag with plastic clips

Accessory bag with INOX clips

The products in this catalogue are OEM components requiring final assembly by a qualified OEM manufacturer. Data subject to change.



Housing



	Order nu	mber	đ	KG		
	With plastic clips	With INOX clips	Units/Box	Box	Box/Pallet	Box/Pallet
1 x 0.6	10012916	10012919	72	51	8	8
1 x 1.2	10012920	10012925	72	78	4	4
1 x 1.5	10012926	10012930	72	98	4	4
2 x 0.6	10012932	10012935	40	39	8	8
2 x 1.2	10012936	10012940	40	59	4	4
2 x 1.5	10012941	10012944	40	77	4	4

Gear tray

		Order number	ð	KG		P
		Т8	Units/Box	Box	Box/Pallet	Box/Pallet
	1 x 0.6	10013279	500	130	2	2
-	1 x 1.2	10013281	500	261	1	1
	1 x 1.5	10013283	500	325	1	1
	2 x 0.6	10013285	250	101	2	2
	2 x 1.2	10013286	250	195	1	1
	2 x 1.5	10013288	250	260	1	1

Diffuser

	Order n	umber		KG		B
	PC	PMMA	Units/Box	Box	Box/Pallet	Box/Pallet
1 x 0.6	10012909	10013000	125	30	8	8
1 x 1.2	10012910	10013002	125	59	4	4
1 x 1.5	10012911	10013004	125	70	4	4
2 x 0.6	10012912	10013005	70	25	8	8
2 x 1.2	10012913	10013007	70	42	4	4
2 x 1.5	10012914	10013009	70	54	4	4

Accessories

Accessory bag					Mounting accessories
Clasing aline	Lu	uminaire length	m	Single	Suspension kit
Closing clips	0.6	1.2	1.5	clip	414551
Plastic	10022536	10022535	10022534	17172	
INOX	429411	50027015	50027016	30004739	0000
	_				0-0



Accessory bag with plastic clips



Accessory bag with INOX clips

ACCESSORIES





Resistance to chemical agents

Chemical agents	Polyester	Polycarbonate	Aluminium	PMMA	Stainless stee
Acetic acid 10%	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark
Acetone	Ø	х	\checkmark	х	\checkmark
Alcoholic beverages	1	\checkmark	\checkmark	Ø	\checkmark
Aluminium sulphate	\checkmark	\checkmark	\checkmark	 ✓ 	Ø
Ammonia 5%	ø	х	\checkmark	\checkmark	- V
Aniline	Ø	X	\checkmark	Х	\checkmark
Arsenic acid 20%	ø	√ 	\checkmark	√ √	\checkmark
Benzene	X	х	\checkmark	Х	Ø
Bencylic alcohol	X	x	ø	X	ø
Bromine	X	X	X	X	x
Calcium Chloride	\checkmark	× ✓	√ √	 ✓	ø
Calcium nitrate	\checkmark	\checkmark	\checkmark	\checkmark	ø
Carbon tetrachloride	X	x	✓	X	ø
Carbonic acid	√ 	X	\checkmark	X	√
Caustic potash 5%	X	x	X	 ✓	ø
Cement	 ✓	 ✓	 ✓	✓ ✓	ø
Hydrochloric acid 1-5%	ø	✓ ✓	×	✓ ✓	Ø X
Chlorine liquids (vapours)					
Chloroform	X X	X X	X ✓	X	Ø √
Chromic acid				X	
Citric acid 20%	X ✓	ø ✓	X ✓	ø √	Ø
Copper sulphate	v √	✓ ✓		v √	
	✓ ✓		X ✓	✓ ✓	Ø √
Diesel-naphta oil	✓ ✓	Ø V	✓ ✓		∨
Ethyl alcohol 30%				Ø	 ✓
Ethyl chloride	X ✓	Х	Ø	Х	
Ethyl ether	✓ ✓	Х	√	X	Ø
Food oils and fats		X	\checkmark	√	√
Formic acid 10%	Ø	√	X	√	Ø
Glycerine	\checkmark	 ✓ 	√	√	√
Hexane	Ø	\checkmark	\checkmark	√	\checkmark
lodine	✓	Х	Ø	\checkmark	Х
Isopropylic alcohol	√	Ø	√	Ø	Ø
Lubricating oil	√	~	✓	✓	✓
Magnesium sulphate	\checkmark	\checkmark	\checkmark	\checkmark	✓
Methanol	\checkmark	Х	\checkmark	Ø	\checkmark
Mineral oils	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark
Nitric acid 20%	Х	Ø	Х	\checkmark	\checkmark
Oxygen	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark
Ozone	\checkmark	\checkmark	\checkmark	\checkmark	Ø
Perchloric acid 10%	Х	\checkmark	Х	\checkmark	Х
Petrol	\checkmark	Х	\checkmark	\checkmark	\checkmark
Phenol	Ø	Х	\checkmark	х	Ø
Pothassium bromide	\checkmark	\checkmark	ø	\checkmark	Ø
Pothassium nitrate	\checkmark	\checkmark	\checkmark	\checkmark	Ø
Pothassium permanganate	\checkmark	\checkmark	\checkmark	\checkmark	ø
Sea climate	\checkmark	\checkmark	Ø	\checkmark	Ø
Silicon oils	\checkmark	\checkmark	\checkmark	Ø	\checkmark
Soda bleach 15%	\checkmark	Х	Ø	\checkmark	ø
Sodium chloride	\checkmark	\checkmark	ø	\checkmark	ø
Sodium hydroxide 5%	\checkmark	Х	x	\checkmark	ø
Sodium sulphate	\checkmark	✓	✓	\checkmark	ø
Sugar	\checkmark	\checkmark	\checkmark	\checkmark	√
Sulphur	\checkmark	✓	\checkmark	\checkmark	ø
Sulphuric acid 30%	Х	\checkmark	X	\checkmark	X
Toluene	X	x	✓	X	✓ ✓
Trichloroethylene	X	x	\checkmark	X	ø
Zinc sulphate	 ✓	∧ ✓	ø	\checkmark	Ø

✓ ResistantØ Relatively resistant

x Non-resistant

This is a recommendation about the compatibility of equivalent or similar chemical agents included in the composition of the cleaning products with the polymers present in the luminaires. It is based on information from material suppliers, available documentation, tests and our experience in different applications.

Materials resistance can be also affected by concentration, temperature, presence of various chemicals, solvent evaporation and other factors, so this table must be considered as a general reference. Product compliance must be determined by the customer for each specific use.

Technical Information

Ingress protection: IP

The protection of luminaires against the penetration of dust, solid matter and dampness is in accordance with UNE-EN 60529:2018 standard¹.

↓ IP<mark>6</mark>6

Protection against the penetration of solid matter and dust.

0	Unprotected
1	Protected against solid matter greater than 50 mm
2	Protected against solid matter greater than 12 mm
3	Protected against solid matter greater than 2.5 mm
4	Protected against solid matter greater than 1 mm (e.g. small tools, small cables, etc.)
5	Protected against dust (without damaging sediment)
6	Protected against dust

Impact protection: IK



00	Unprotected
01	Impact Energy 0.15 Joules
02	Impact Energy 0.20 Joules
03	Impact Energy 0.35 Joules
04	Impact Energy 0.50 Joules
05	Impact Energy 0.70 Joules
06	Impact Energy 1 Joule
07	Impact Energy 2 Joules
80	Impact Energy 5 Joules
09	Impact Energy 10 Joules
10	Impact Energy 20 Joules

↓ IP66

Protection against the penetration of liquids.

0	Unprotected
1	Protected against vertical water splashes (condensation)
2	Protected against water splashes of up to 15° of the vertical
3	Protected against water splashes of up to 60° of the vertical
4	Protected against water projections in all directions
5	Protected against water assault in all directions
6	Protected against water assault similar to heavy seas
7	Protected against immersion
8	Protected against prolonged effects of underwater immersion
9K ²	Protected against high-pressure / steam-jet cleaning'.

²The third figure K is in accordance with ISO 20653:2013 standard, related to the protection of electrical equipment against foreign objects, water and access.



Our acceptance of an order entails, in any event, that the buyer accepts the following general conditions of sale and supply:

1. Source of supply

ZALUX luminaires can be obtained through our established network of distributors in the different countries.

2. Offers

The written, oral and telephone offers are without compromise. The delivery of offers does not oblige us to accept the order. All orders and compromises are only valid if we have expressly ratified them in writing.

3. Prices

The prices of the Price List in force are understood to be for materials in stock. We reserve the right to modify the prices; if it is possible, said variation will be communicated in the best possible time.

4. Delivery time

Delivery time will be confirmed individually once the order is accepted. Delivery time set by ZALUX, S.A., will be respected and only modified due to production or force majeure. Delay will be communicated to the customer in advance, for his approval. Delivery delays will not allow the buyer to neither cancel the order nor to apply any penalty nor indemnifications for it, except for the case that it has been specifically agreed in advance.

5. Orders

ZALUX, S.A., can unilaterally annul current orders, if the circumstances of a main force that impede their completion should occur. Understood as circumstances of a main force: industrial disputes, labour disruptions, shortage of raw materials, etc. The buyer cannot annul orders for specially made materials without our written agreement. In case of acceptance on our part the expenses incurred up to the moment of cancellation will be charged to the buyer.

6. Packaging

The products are sold in their original cardboard package. Under certain circumstances or the buyer indicates to us to use another package, it will be charged to the buyer at its cost price.

7. Transport

With the delivery of the merchandise to the transport agency the delivery is considered to have been correctly made. The risks of transport of the consignment of our products are on the buyers' account. They can only reclaim from the transport agency for the damages incurred during transport. We will with the utmost pleasure collaborate and support their reclamation with details, etc.

8. Measurements

The measurements are given in millimetres in the descriptions of the models. We reserve the right to introduce small deviations in the measurements as well as modifications due to improvements to the models. The price would be susceptible to variation in this case.

General sale conditions

9. Reclamations

Reclamations relative to numerous faults and defects will only be valid if the proper reclamation has been sent within the seven days as from the reception of the merchandise. If the reclamation is founded and the merchandise is in its original state, the corresponding acceptance will be sent.

10. Return of material

Return of material will not be accepted for reasons of mistaken instructions, shapes, quantities or material to be repaired, if we have not previously given our written authorisation. Those returns must be sent DDP ZALUX and 30% demerit of the original value will be applied. We do not accept the return of specially made products.

11. Property rights

In all cases and even against a third party, ZALUX, S.A., conserves full ownership of all the supplied materials, in the case that the agreed payment has not been settled.

12. Patent rights

All the models in this catalogue are protected by law. Legal action with right to redemption will be taken against anyone making imitations.

13. Reprints

Total or partial reproduction of this catalogue is forbidden without the corresponding written authorisation of ZALUX, S.A.

14. Payment

The form of payment will be established at the time of making a firm order for the merchandise, in accordance with the usual standards in ZALUX, S.A.

15. Jurisdiction

For any question that could arise in the completion or interpretation of these general rules, the contracting parties, with expressly renouncing any local law code that could correspond to them, will be submitted expressly to the Magistrate Law Courts of Zaragoza.

16. Modifications

ZALUX, S.A. in its continuous improvement process, reserves the right to modify its technical specifications without any previous notice.

The buyer is responsible that the product purchased in components, once fully wired, meets the requirements of the respective country.



ZALUX, S.A. Avda. Manuel Rodríguez Ayuso, 114 Centro Empresarial Miralbueno Planta 1ª – Local P2. E-50012 Zaragoza, Spain Tel.: +34 976 462 200 info@zalux.com



www.zalux.com