

PRODUCT NO. 4732-OFW110

## DOTLUX Tracklight STICKtrack 30W 1,2m COLORselect black



to the product page

- One part number - three light colors adjustable by COLORselect
- Natural color perception due to extra high CRI>95 value
- Compact design, ideal for low room heights
- Uniform light distribution for optimum ambient lighting
- Benefit from the large-area illumination of a light band with simple installation in your track rail

|                                    |           |   |                          |
|------------------------------------|-----------|---|--------------------------|
| <b>SUCCESSION ARTICLE</b>          | -         | <b>BEAM ANGLE</b>   | 110°                     |
| <b>WEIGHT IN KG</b>                | 0.76      | <b>PROTECTION CLASS (IP)</b>  | IP20                     |
| <b>POWER CONSUMPTION IN WATTS</b>  | 30        | <b>INPUT VOLTAGE</b>  | 176 - 240 V AC/DC        |
| <b>NET LUMINOUS FLUX IN LUMENS</b> | max. 3060 | <b>SERVICE LIFE</b>   | approx. 50.000 h at 25°C |
| <b>LUMEN PER WATT</b>              | 102       | <b>COLOR TEMPERATURE IN KELVIN</b>  | 3000/4000/5700           |
|                                    |           | <b>POWER SUPPLY</b>   | Integrated               |
|                                    |           | <b>COLOR-RENDERING-INDEX</b>  | CRI > 95                 |
|                                    |           | <b>POWER FACTOR</b>   | 0,9                      |
|                                    |           | <b>INRUSH CURRENT IN A</b>  | 0                        |
| <b>Dimensions</b>                  |           | <b>SPECIAL FEATURE</b>  | Flicker-free             |
| <b>length:</b> 1240mm              |           | <b>LUMEN PER WATT</b>   | 102                      |
| <b>width:</b> 32mm                 |           | <b>PROTECTION CLASS</b>   | I                        |
| <b>height:</b> 52mm                |           | <b>HOUSING COLOUR</b>   | black                    |
|                                    |           | <b>SUITED FOR EMERGENCY LIGHTING</b>  | yes                      |
|                                    |           | <b>COVER MATERIAL</b>   | Polycarbonate PC         |
|                                    |           | <b>WARRANTY IN YEARS</b>  | 3                        |
|                                    |           | <b>HOUSING MATERIAL</b>   | Aluminium                |
|                                    |           | <b>L/B VALUE</b>  | L70/B50                  |
|                                    |           | <b>SUITED FOR EMERGENCY POWER</b>   | -                        |
|                                    |           | <b>SIMILAR TO RAL-COLOUR</b>  | 9005                     |
|                                    |           | <b>ENABLED LICENSED PRODUCT</b>   | Yes                      |
|                                    |           | <b>ASSORTMENT</b>   | Proline                  |
|                                    |           | <b>ENERGY EFFICIENCY CLASS<br/>ACCORDING TO EU REGULATION<br/>2019/2015</b> | not required             |
|                                    |           | <b>ETIM GRUPPEN-ID</b>  | EC001744                 |
|                                    |           | <b>DIMMING 0-10 V</b>   | Nein                     |

|  |       |
|--|-------|
| <b>DIMMING 1-10 V</b>                            | Nein  |
| <b>DIMMING DALI</b>                              | Nein  |
| <b>DIMMING DMX</b>                               | Nein  |
| <b>DIMMING DSI</b>                               | Nein  |
| <b>DIMMING POTENTIOMETER (INTEGRATED)</b>        | Nein  |
| <b>DIMMING LINESWITCH</b>                        | Nein  |
| <b>DIMMING MANUFACTURER'S PROPRIETARY SYSTEM</b> | Nein  |
| <b>DIMMING MAINS VOLTAGE MODULATION</b>          | Nein  |
| <b>DIMMING PHASE CUT-OFF</b>                     | Nein  |
| <b>DIMMING PROGRAMMABLE</b>                      | Nein  |
| <b>DIMMING RF</b>                                | Nein  |
| <b>DIMMING SINE WAVE REDUCTION</b>               | Nein  |
| <b>DIMMING TOUCH AND DIM</b>                     | Nein  |
| <b>DIMMING ZIGBEE</b>                            | Nein  |
| <b>DIMMING WITH PUSH-BUTTON</b>                  | Nein  |
| <b>DIMMING DEPENDING ON CONTROL GEAR</b>         | Nein  |
| <b>NO DIM FUNCTION</b>                           | Yes   |
| <b>COLOUR CONSISTENCY (MCADAM ELLIPSE)</b>       | SDCM6 |
| <b>SUITABLE FOR EMERGENCY LIGHTING</b>           | Yes   |
| <b>DIMMING DALI-2</b>                            | Nein  |
| <b>DIMMING PHASE CUT-ON</b>                      | Nein  |
| <b>DIMMING GPRS</b>                              | Nein  |
| <b>PULSE DURATION IN µS</b>                      | 0     |