



LED light point, IP44
Artikel-Nr. 12079073

Licht.
Für Generationen.



Tender	
LED light point, IP44, white, round. In a compact design, for installation in tool-less rapid assembly systemsLamp holder: Plug&Play, Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Stainless steel / Aluminium / Plastic, Degree of protection: according to DIN EN 60529 IP44*, Protection class: (EN 61140) III, Current: 350 mA, Power: 3.3W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 160lm, Colour temperature: 3.000 K, Light colour : White, Beam angle: 32°, Adjustability: Not adjustable, With control gear: No, Control: Dimming depending on driver.	

Article data	
Artikel-Nr.	12079073
GTIN	4250047797012
Kurzbeschreibung	LED light point, IP44
Material	Stainless steel / Aluminium
Colour	White
Type of surface	Matt
Shape	round
Outer diameter	50 mm
Built-in diameter	38 mm
Installation depth	35 mm
weight	0.056 kg

LED light point, IP44

Artikel-Nr. 12079073

Licht.
Für Generationen.

Lighting technology	
Colour temperature	3000 K
Light colour	White
Light output	Direct
Luminous flux	160 lm
System efficiency	48 lm/W
Colour rendering	CRI > 80
Reflector	Without
Beam angle	32 °
Light sharing	Symmetric

Operating technology of the luminaires	
System output	3.3 W
Voltage type	DC
Current	350 mA
Lamp	LED
Lamp holder	Plug&Play
Protection class	III
Degree of protection	IP44
Schutzart deckenseitig	IP20
Converter - possible luminaire 1 pc.	17666 17662 17613 17621 17663 17648
Control	Dimming depending on driver
Leuchtmittelwechsel möglich	ja

Mounting technology	
Mounting method	Recessed mounting
Place of installation	Ceiling-mounted
Adjustability	Not adjustable
Further references	No cover with thermal insulation material
Material cover	Plastic, structured

Packing data	
Gross weight	0.072 kg
Length of packaging	72 mm
Packaging width	72 mm
Packaging height	48 mm

LED light point, IP44

Artikel-Nr. 12079073

Licht.
Für Generationen.

Accessories	
	Artikel-Nr.: 17666000 Kurzbeschreibung: LED converter 350 mA, on/off Leistung: 1 - 5 W Abmessung: 52 mm x 30 mm x 23 mm
	Artikel-Nr.: 17662020 Kurzbeschreibung: LED converter 350 mA, on/off Leistung: 1 - 7,2 W Abmessung: 68 mm x 35 mm x 21 mm
	Artikel-Nr.: 17613000 Kurzbeschreibung: LED converter 350 mA, on/off Leistung: 1 - 15 W Abmessung: 115 mm x 34 mm x 19 mm
	Artikel-Nr.: 17621020 Kurzbeschreibung: LED converter 350 mA, on/off Leistung: 1 - 21 W Abmessung: 128 mm x 50 mm x 13 mm
	Artikel-Nr.: 17663020 Kurzbeschreibung: LED converter 350 mA, trailing-edge phase dimmable Leistung: 2,8 - 7 W Abmessung: 110 mm x 50 mm x 19 mm
	Artikel-Nr.: 17648020 Kurzbeschreibung: LED converter 350 mA, trailing-edge phase dimmable Leistung: 0,7 - 17 W Abmessung: 166 mm x 46 mm x 34 mm