



Product Service

CERTIFICATE

No. U6 18 01 84117 051

Holder of Certificate: Osram GmbH

Marcel-Breuer-Str. 6
80807 München
GERMANY

Certification Mark:



Product:

**Electronic controlgear for LED modules
(24V Constant Voltage LED Power Supply)**

The product was voluntarily tested according to the listed standards. The product can be marked with the certification mark shown above. The certification mark must not be altered in any way. See also notes overleaf.

Test report no.:

64142170524201



Date, 2018-01-15


(Richard Xu)

Page 1 of 2



Product Service

CERTIFICATE**No. U6 18 01 84117 051****Model(s):**

OT 20/220-240/24 DIM P, OT 20/220-240/24 P,
 OT 40/220-240/24 DIM P, OT 40/220-240/24 P,
 OT 60/220-240/24 DIM P, OT 60/220-240/24 P

Brand Name:**OSRAM****Parameters:**

Rated Input: 220-240VAC, 50/60Hz or 176-250VDC
 Protection against Electric Shock: Class II; SELV
 Degree of Protection: IP66
 Method of Installation: Independent
 Type of Output: Constant voltage type
 ta: -30~50°C (OT 60/220-240/24 DIM P,
 OT 60/220-240/24 P);
 -30~55°C (other models)
 tc: 85°C (OT 20/220-240/24 DIM P,
 OT 20/220-240/24 P);
 90°C (other models)
 Rated output voltage: 24VDC
 Max. output voltage: 30VDC

Model	Rated max. output current (mA)
OT 20/220-240/24 DIM P	830
OT 20/220-240/24 P	830
OT 40/220-240/24 DIM P	1670
OT 40/220-240/24 P	1670
OT 60/220-240/24 DIM P	2500
OT 60/220-240/24 P	2500

Model	Rated max. output power (W)
OT 20/220-240/24 DIM P	20
OT 20/220-240/24 P	20
OT 40/220-240/24 DIM P	40
OT 40/220-240/24 P	40
OT 60/220-240/24 DIM P	60
OT 60/220-240/24 P	60

Tested according to:

EN 61347-1:2015
 EN 61347-2-13:2014/A1:2017
 EN 62384:2006/A1:2009

Production Facility(ies):

59266