

# CERTIFICATE

No. U6 101524 0080 Rev. 00

**Holder of Certificate:** **Hunan Xiezheng Electronics Co., Ltd.**

Block A&B, Building 11. Innovation Park  
Linyi Road, Bailutang Town  
Suxian District  
423038 Chenzhou, Hunan  
PEOPLE'S REPUBLIC OF CHINA

**Certification Mark:**



**Product:**

**Power supply  
(LED POWER SUPPLY)**

The product was voluntarily tested according to the listed standards. The product can be marked with the certification mark shown above. It is not permitted to alter the certification mark in any way. In addition, the certificate holder must not transfer the certificate to third parties. All applicable requirements of the testing and certification regulations of TÜV SÜD Group have to be complied. For details see: [www.tuvsud.com/ps-cert](http://www.tuvsud.com/ps-cert)

**Test report no.:**

64142220463101

**Date,** 2022-12-01



( Richard Xu )

# CERTIFICATE

No. U6 101524 0080 Rev. 00

**Model(s):** ID LCCB 35/230/100-850 DALI NFC FV1,  
 ID LCCB 40/230/250-1050 DALI NFC FV1,  
 ID LCCB 50/230/350-1400 DALI NFC FV1,  
 ID LCCB 60/230/500-1650 DALI NFC FV1,  
 ID LCCB 75/230/700-2000 DALI NFC FV1,  
 ID LCCB 100/230/900-2200 DALI NFC FV1

**Brand Name:** cupower



**Parameters:** Rated Voltage / Rated Frequency: 220-240VAC, 50/60Hz  
 or 220-240VDC  
 Rated input current: See model list  
 Rated output: See model list  
 Protection against Electric Shock: SELV  
 Degree of Protection: IP20  
 Method of Installation: Built-in  
 Type of Output: Constant current  
 ta, tc: See model list

**Tested according to:** EN 61347-1:2015/A1:2021  
 EN 61347-2-13:2014/A1:2017  
 EN IEC 62384:2020

**Production Facility(ies):** 101524

# CERTIFICATE

No. U6 101524 0080 Rev. 00

## Model list

Item No.	Model	Rated input current (A)	PF	Rated output voltage (VDC)	Rated output current (mA)	Uout (VDC)	Max. rated output power (W)	ta/tc (°C)
1	ID LCCB 35/230/100-850 DALI NFC FV1	Max. 0.21	0.9C	15-54	100-850	60	35	-20 to +50/80
2	ID LCCB 40/230/250-1050 DALI NFC FV1	Max. 0.24	0.9C	15-54	250-1050	60	40	-20 to +50/80
3	ID LCCB 50/230/350-1400 DALI NFC FV1	Max. 0.3	0.9C	15-54	350-1400	60	50	-20 to +50/85
4	ID LCCB 60/230/500-1650 DALI NFC FV1	Max. 0.35	0.9C	15-54	500-1650	60	60	-20 to +50/85
5	ID LCCB 75/230/700-2000 DALI NFC FV1	Max. 0.43	0.9C	15-54	700-2000	60	75	-20 to +50/85
6	ID LCCB 100/230/900-2200 DALI NFC FV1	Max. 0.55	0.9C	15-54	900-2200	60	100	-20 to +50/85