



Circular Plug Connectors IP68  
Circular Plug Connectors AC 167 micro  
**AC 167 RBU/ 2**



Socket, 2 pole, Voltage Rating: 250 V, Current Rating: 10.0 A

### Order Info

<b>Reference Number (ref. no.)</b>	72506216
<b>Applications</b>	Lighting, Installation
<b>PU</b>	200
<b>EAN</b>	4028012130320

### Type

<b>Type</b>	Socket
<b>Number of poles</b>	2 pole
<b>Clamping Units per Pole</b>	1
<b>Colour</b>	black
<b>Connection Type</b>	Screw
<b>Protection Against Incorrect Plugging</b>	yes

### Technical Data

<b>Voltage Rating</b>	250 V
<b>Current Rating</b>	10.0 A
<b>Insulating Material</b>	PA 6.6
<b>Contact Material</b>	Brass
<b>Core Cross-Section min.</b>	0.25 mm <sup>2</sup>
<b>Core Cross-Section max.</b>	1.0 mm <sup>2</sup>
<b>Flammability Rating</b>	V-2
<b>max. Ambient Temperature Operation</b>	85 °C
<b>IP Code</b>	IP68
<b>Type of Conductor Solid</b>	yes
<b>Type of Conductor Flexible</b>	yes
<b>Type of Conductor Stranded</b>	yes
<b>Stripping Length</b>	6.0 mm
<b>Assembly Contact Screw</b>	0.5x3.0 / ⌀ 2.0 Nm
<b>Assembly Strain Relief</b>	⌀ 2.5 Nm
<b>Cable Diameter min.</b>	5.8 mm
<b>Cable Diameter max.</b>	6.9 mm
<b>Strain Relief</b>	yes

## Accessories

<b>AC 167 WKZ</b>	729041
<b>AC 169 BC black</b>	729030
<b>AC 167 RVKB M16</b>	729043
<b>AC 167 RVKS M16</b>	729042