

Floodlight without sensor

# LS 150

white

EAN 4007841 069223

Article number 069223



LED

30 years (Ø 4,5h / day)

4000 K

4000K neutral white



IP44

3 years

manufacturer's warranty  
steinel.de/garantie3y



CE



energy saving



plastic free packaging



Light source not exchangeable



Control gear not exchangeable

## Function description

Beautiful. Bright. Ideal for courtyards and driveways: the LS 150 M LED spotlight without sensor. Neutral white light (4,000 K), {luminous flux}, 14,7 W. Adjustable 80° horizontally and 150° vertically. The spotlight is switched on and off manually by a switch. Protection class IP 44. Colour version: black and white.

## Technical specifications

Dimensions (L x W x H)	167 x 157 x 178 mm
Mains power supply	220 – 240 V / 50 – 60 Hz
Output	14,7 W
Interconnection	No
Lichtstrom Gesamtprodukt	1375 lm
Efficiency (without shade/diffuser)	77 lm/W
Gesamtprodukt Effizienz	94 lm/W
Colour temperature	4000 K
Colour variation LED	SDCM3
Colour Rendering Index	80-89
With lamp	Yes, STEINEL LED system
Lamp	LED cannot be replaced
LED life expectancy (max. °C)	50000 h
Base	without

LED cooling system	Passive Thermo Control
With motion detector	No
Basic light level function	No
Main light adjustable	No
Soft light start	No
Impact resistance	IK03
IP-rating	IP44
Protection class	I
Ambient temperature	-10 – 30 °C
Housing material	Aluminium
Manufacturer's Warranty	3 years
Installation site	wall
Version	white
PU1, EAN	4007841069223

Floodlight without sensor

# LS 150

white

EAN 4007841 069223

Article number 069223



## Dimension Drawing

