

CERTIFICATE ENEC/FI 2017085



Our Ref. 289321-1

Product Electronic control gear for LED module

Rating and principal characteristics See page 2

Trade mark (if any) HELVAR

Types LC1x30-E-DA, LC1x30-E-DA Active, LC1x30-E-DA+LC1x30-SR, LC1x30-E-DA-nDim, LC1x30-E-DA-nDim+LC1x30-SR, LC1x30-E-DA Coated, LC1x30-E-DA Coated+LC1x30-SR

Name and address of the licensee and the manufacturer
 Helvar Oy Ab
 Keilaranta 5
 FI-02150 ESPOO
 FINLAND

Is in conformity with EN 61347-2-13:2014 + A1:2017
 EN 61347-1:2015
 EN 62384:2006 + A1:2009

As shown in the Test Report(s) No(s) 289321-1A, 289321-1B

It is authorized to use of the marks ENEC 16 and FI

Validity This certificate is valid until 28 December 2022 provided that the Conditions for ENEC and FI certification are met. This certificate includes the right to use the ENEC 16 and FI mark under the condition that product changes (if any) will be approved at SGS Fimko before the product is brought onto market.

Directive information The certified product(s) fulfils requirements of above mentioned standard(s) which are harmonised under the Low Voltage Directive (2014/35/EU) at the date of issue of the certificate.

With the following limitations -

Date of issue 28 December 2017

SGS Fimko Ltd

Signature

Jonas Leinonen
 Specialist



This certificate has 3 pages



This certificate is issued by the company under its General Conditions for Certification Services accessible at <http://www.sgs.fi/en/Terms-and-Conditions.aspx>. Attention is drawn to the limitations of liability defined therein and in the Test Report here above mentioned which findings are reflected in this certificate. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Rating and principal characteristics LC1x30-E-DA, LC1x30-E-DA Active, LC1x30-E-DA+LC1x30-SR:
 220-240VAC; 50-60Hz; Constant current: 350mA / 10...60V / Prated 21 W
 or 500mA / 10...60V / Prated 30W or 700mA / 10...43V / Prated 30W;
 tc +75° C; λ 0,93...0,96; U-OUT: 80V;
 ta: -20...+50°C / -20...+45°C (built-in / independent); SELV

LC1x30-E-DA-nDim, LC1x30-E-DA Coated, LC1x30-E-DA Coated
 +LC1x30-SR, LC1x30-E-DA-nDim+LC1x30-SR:
 220-240VAC; 50-60Hz; Constant current: 350mA / 10...60V / Prated 21 W
 or 500mA / 10...60V / Prated 30W or 700mA / 10...43V / Prated 30W;
 tc +75°C; λ 0,93...0,96; U-OUT: 80V;
 ta: -40...+50°C / -40...+45°C (built-in / independent); SELV

Independent usage with LC1x30-SR.



Page No.: 3 of Certificate No.: ENEC/FI 2017085

Manufacturing site(s)

Helvar Oy Ab
Yrittäjätie 23
FI-03600 KARKKILA
FINLAND

JLE