


Technical Data

Designation	LED control gear
Output characteristic	Constant current
Output voltage	5 - 40 V
Output current	350 / 500 / 700 mA, selectable
Output power	2 - 15 W
No. of output channels	1
Output pwm frequency	n.a.
<hr/>	
Input voltage	220 - 240 V, 0 / 50 - 60 Hz
Power factor	0.95 at full load
Efficiency	0.87 at full load
Input voltage range a.c.	198 - 264 V
Input voltage range d.c.	176 - 276 V
No. of ECG per circuit breaker	50 pcs. at type B16
Ambient temperature range ta	- 25 °C to 60 °C
Max. case temperature tc	75 °C
Average lifetime	> 50.000 h at tc = 75 °C
<hr/>	
Approval marks	
Interface	n.a.
Control current	n.a.
Dimming range	n.a.
<hr/>	
Wire cross-section	0.5 to 1.5 mm ² / 0.2 to 0.5 mm ²
Order number	3 C 115 17 0

Dimensions

Length x Width x Height	80 x 40 x 22 mm
Mounting holes distances D1, D2	71, 68 - 75 mm
Weight	ca. 0.065 kg
Packaging unit	44 pcs.

Product features

- SELV output
- Short-circuit and no-load protection with automatic restart
- Suitable for central battery emergency lighting systems

