

PRODUCT DATASHEET

DP HOUSING 1500 1x Lamp IP65

DAMP PROOF HOUSING | Damp-proof luminaire for T8 LED lamps



Product benefits

- Prewired for easy installation of tubular AC LED lamps
- Robust housing
- Easy and quick installation
- 5 years guarantee

Product features

- Luminaire housing, available for 1 or 2 T8 LED lamps
- Type of protection: IP65
- Suitable for SubstiTUBE EM/UN and SubstiTUBE Connected



TECHNICAL DATA

Electrical data


| | |
|--|-------------|
| Nominal voltage | 220...240 V |
| Mains frequency | 50...60 Hz |
| Max. no. of lum. on circuit break. B16 A | - |
| Max. no. of lum. on circuit break. C16 A | - |
| Protection class | IK08 |

Photometrical data

| | |
|---------------------------------|-------|
| Flickering metric (Pst LM) | - |
| Stroboscope effect metric (SVM) | - |
| Beam angle | 105 ° |

Dimensions & Weight

| | |
|----------------|------------|
| Length | 1561.00 mm |
| Width | 64.00 mm |
| Height | 75.00 mm |
| Product weight | 1300.00 g |



Materials & Colors

| | |
|--|--------------------|
| Product color | Grey |
| Housing color | Gray |
| Body material | Polycarbonate (PC) |
| Cover material | Polycarbonate (PC) |
| Light emitting surface material | Polycarbonate (PC) |
| Glow Wire Test according to IEC 60695-2-12 | 650 °C |
| Mercury content | 0.0 mg |

Application & Mounting

| | |
|---------------------------|--------------|
| Ambient temperature range | -20...+45 °C |
|---------------------------|--------------|

| | |
|--|----------------|
| Temperature range at storage | -20...80 °C |
| Type of connection | Screw terminal |
| Type of protection | IP65 |
| Protection class IK (shock resistance) | IK08 |
| Dimmable | No |
| Mounting type | Surface |
| Mounting location | Ceiling |
| Application environment | Indoor |
| With light source | No |




Certificates & Standards

| | |
|--|---------------------------------|
| Standards | CE / TÜV Rheinland / EAC / RoHS |
| Luminaire with limited surface temperature, "D sign" | No |
| Ball shot safe | No |

EQUIPMENT / ACCESSORIES

- All required accessories included

DOWNLOAD DATA

| DOWNLOAD DATA | |
|--|----------------------------|
|  | User instruction |
|  | Tender documents |
|  | Declarations of conformity |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075312487 | Shipping box 6 | 1,582 mm x 235 mm x 182 mm | 9655.00 g | 67.66 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

– For Guarantee see www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.