

Presence detector - Professional Line

IR Quattro SLIM 4m

V3 KNX

EAN 4007841 058494

Article number 058494



infrared sensor
max. 4 x 4m
presence



max. 4 x 4 m
presence



KNX 4 channel



10 - 1000 lux with
RC 6



1 min - 15 min
with RC 6



ideal 2,5 - 4 m



indoor sensor

Teach

Teach mode with
RC 6

iQ

iQ-mode

5 years

manufacturer's
warranty
[steinel-professional.de/garantie](https://www.steinel.de/garantie)

Function description

Genuine 16 m² of presence detection concentrated on 4 mm. Control PRO IR Quattro SLIM KNX presence detector for indoors, ideal for small offices, store, service and utility rooms, washrooms and WCs, for mounting at a height of up to 4 m, with digital BUS interface for controlling 4 lighting channels and HVAC.

IR Quattro SLIM 4m

V3 KNX

EAN 4007841 058494

Article number 058494



Technical specifications

Type	Presence detector
Dimensions (L x W x H)	55 x 77 x 77 mm
Power supply, detail	KNX bus
Sensor Technology	passive infrared
Application, place	Indoors
Installation site	ceiling
Installation	In-ceiling installation
Mounting height	2,50 – 4 m
Reach, radial	4 x 4 m (16 m ²)
Reach, tangential	4 x 4 m (16 m ²)
Reach, presence	4 x 4 m (16 m ²)
Reach, detail	Retina lens and hexagonal Fresnel structure
Detection angle	360 °
Angle of aperture	71 °
Switching zones	260 switching zones
Optimum mounting height	2,8 m
Mechanical scalability	No
Sneak-by guard	Yes
Capability of masking out individual segments	No
Electronic scalability	No
Twilight setting TEACH	Yes

Twilight setting	10 – 1000 lx
Time setting	10 s – 1092 Min.
Constant-lighting control	No
Basic light level function	Yes
KNX functions	Photo-cell controller, Basic light level function, Light level, HVAC output, Constant-lighting control, Light output 4x, Presence output, Day / night function, Logic gate
With bus coupling	Yes
Settings via	ETS software, Remote control, Bus, Smart Remote
With remote control	No
Interconnection	Yes
Type of interconnection	Master/master, Master/slave
IP-rating	IP20
Material	Plastic
Ambient temperature	0 – 40 °C
Application, room	one-person office, hotel room, care room, function room / ancillary room, WC / washroom, Indoors
Colour	white
Colour, RAL	9010
Manufacturer's Warranty	5 years
Version	KNX
PU1, EAN	4007841058494
Technology, sensors	passive infrared, Photo-cell controller

Accessories

EAN 4007841 009151	Remote control Smart Remote
EAN 4007841 593018	Service remote control RC6 KNX
EAN 4007841 592912	User remote control RC7 KNX

Presence detector - Professional Line

IR Quattro SLIM 4m


V3 KNX

EAN 4007841 058494

Article number 058494



Detection Zone



Mögliche Montagehöhe: 2,50 m – 4,00 m

Orange: Präsenz, tangential und radial

Dimension Drawing

