



Product features and key data

LED-System	YY
Photobiological class	YY
Ingress Protection (IP) rating	IP54
Ambient temperature	-20 - 50 °C
Net length	95 mm
Net width	95 mm
Net height	65 mm
Weight	0,2 kg

Offer text

LiveLink sensor unit with integrated PIR presence sensor for connecting to a LiveLink control unit, for high-resolution presence detection. Version specifically for use in distribution centres and highbay racking. Connection and electrical supply via the DALI interface of the LiveLink control unit. Passive infrared presence sensor, with 2 high-sensitivity pyro-sensors, settable switch-off delay time, optionally in automatic mode (automatic on, automatic off) or semi-automatic mode (automatic off, manual on). Special IQ mode for automatic adaptation of delay time to room use. Temperature range: -25°C - +55 °C. 2 high-sensitivity pyro sensors ensure maximum detection quality. Presence range of max. 30 m x 4 m in the radius at a mounting height of 14 m enables the detection of minimal movements, permissible mounting height 4 m to 14 m. IP54 protection rating. Surface mounted. Connection and electrical supply via the DALI interface of the LiveLink control unit (occupies 3 DALI devices). No additional mains connection required. Commissioning is via secure WLAN connection (WPA2 encryption) with the LiveLink control unit using the LiveLink Install App and a Tablet PC (iOS/Android). Range reduction is possible with use of a cover shield. Settable parameters: switch-off delay time, semi-/fully automatic, IQ mode activation and range test.