#### Sensor-switched LED floodlight

# **XLED ONE XL S**

Anthracite EAN 4007841 065263 Article number 065263







3000 K







IP44











#### **Function description**

Powerful illumination. Effective protection. The XLED ONE XL S wall and ceiling spot can be tilted through 180° and illuminates its surroundings with day-bright light. In numbers: 3000 K and 4200 lm from 42,6 W. With infrared sensor, 180° angle of coverage, 12 m reach, twilight setting (2-2000 lux) as well as time setting (8 s to 35 min). Protection class: IP44.

## **Technical specifications**

Dimensions (L x W x H)	222 x 259 x 215 mm
Mains power supply	220 – 240 V / 50 – 60 Hz
Sensor Technology	passive infrared
Output	42,6 W
Lichtstrom Gesamtprodukt	4200 lm
Gesamtprodukt Effizienz	99 lm/W
Colour temperature	3000 K
Colour variation LED	SDCM3
Colour Rendering Index	80-89
With lamp	Yes, STEINEL LED system
Lamp	LED cannot be replaced
LED life expectancy (max. °C)	50000 h
LED life expectancy (25 °C)	> 36000 h
Drop in luminous flux in accordance with LM80	L70B10
Base	without
LED cooling system	Passive Thermo Control
With motion detector	Yes
Detection angle	180 °

Capability of masking out individual segments	Yes
Electronic scalability	No
Mechanical scalability	No
Reach, radial	$r = 3 \text{ m } (14 \text{ m}^2)$
Reach, tangential	r = 12 m (226 m <sup>2</sup> )
Photo-cell controller	Yes
Twilight setting	2 – 2000 lx
Time setting	8 s - 35 Min.
Basic light level function	No
IP-rating	IP44
Protection class	I
Ambient temperature	-20 – 40 °C
Housing material	Aluminium
Manufacturer's Warranty	3 years
Settings via	Potentiometers
Installation site	wall, ceiling
Version	Anthracite
PU1, EAN	4007841065263


## Sensor-switched LED floodlight

# **XLED ONE XL S**

Anthracite EAN 4007841 065263 Article number 065263



#### **Detection Zone**



Mögliche Montagehöhe: 1,80 m – 3,00 m

Orange: radial Schwarz: tangential

## **Dimension Drawing**

