

DALI PRO Sensor Coupler

DALI PRO Sensor Coupler | Sensors for light management systems



Areas of application

- Connection of light and presence sensors in DALI systems
- Ceiling or independent installation via ECO CI KIT possible


Product benefits

- Power supply from DALI

Product datasheet

Technical data

Dimensions & weight



Length	118.0 mm
Width	30.0 mm
Height	21.0 mm
Mounting hole spacing, length	110.0 mm
Product weight	35.00 g

Temperatures & operating conditions

Ambient temperature range	0+50 °C
---------------------------	---------

Capabilities

Dimming interface	DALI	
Number of control outputs	1	
Type of installation	Luminaire integration/Ceiling integration	

Certificates & standards

Type of protection	IP20
** .	

Logistical data

Equipment / Accessories

- Suitable for all light and presence sensors from the MULTI 3 range
- Suitable for many OSRAM DALI control systems

Download Data

Product datasheet

File



Declarations of conformity

334811_Declaration of conformity – DALI PRO CONT-4 – DALI PRO PB Coupler – DALI PRO Sen



Installation/Operation notice 334249_Technical instructions

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321379269	DALI PRO Sensor Coupler	Shipping carton box 25	200 mm x 140 mm x 147 mm	4.12 dm ³	1268.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.