PRODUCT DATASHEET ENDURA STYLE UpDown 12 W WT

ENDURA® STYLE UPDOWN | Luminaires with classic shape and light outlet up and down



Areas of application

- Outdoor use (IP44)
- Building facades
- Decorative illumination

Product benefits

- Energy-efficient thanks to LED technology
- Easy and quick installation

Product features

- Very bright and functional outdoor LED luminaires
- Die-cast aluminum housing
- Available in two housing colors



TECHNICAL DATA

Electrical data


| Nominal wattage | 12.00 W |
|------------------------|---------------|
| Nominal voltage | 220240 V |
| Mains frequency | 5060 Hz |
| Nominal current | 70 mA |
| Power factor λ | > 0.5 |
| Protection class | 1 |
| Operating mode | Mains voltage |

Photometrical data

| Luminous flux | 700 lm | |
|--|------------|--|
| Total luminous flux of contained light sources | 1050 lm | |
| Luminous efficacy | 58 lm/W | |
| Color temperature | 3000 K | |
| Light color (designation) | Warm White | |
| Color rendering index Ra | > 80 | |
| Standard deviation of color matching | ≤6 sdcm | |
| Flickering metric (Pst LM) | | |
| Stroboscope effect metric (SVM) | | |
| Beam angle | 100 ° | |

Dimensions & Weight

| Length | 55.00 mm |
|----------------|-----------|
| Width | 90.00 mm |
| Height | 160.00 mm |
| Product weight | 480.00 g |



Materials & Colors

| Product color | White |
|-----------------|----------|
| Housing color | White |
| Body material | Aluminum |
| Cover material | Glass |
| Mercury content | 0.0 mg |

Application & Mounting

| Ambient temperature range | -20+40 °C | |
|------------------------------|-----------------|--|
| Temperature range at storage | -20+85 °C | |
| Type of connection | Screw terminal | |
| Type of protection | IP44 | |
| Dimmable | No | |
| Mounting type | Surface | |
| Mounting location | Wall | |
| Application environment | Outdoor | |
| LED module replaceable | Not replaceable | |
| With light source | Yes | |

Lifespan

| Number of switching cycles | 15000 |
|----------------------------|-------|
|----------------------------|-------|

Certificates & Standards

| Standards | CE / EAC / REACH / RoHS |
|--|-------------------------|
| Luminaire with limited surface temperature, "D sign" | No |

EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included

DOWNLOAD DATA

| | DOWNLOAD DATA |
|-----|------------------|
| PDF | User instruction |



| | DOWNLOAD DATA |
|-----|----------------------------|
| 1 | Tender documents |
| PDF | Declarations of conformity |
| PDF | Packaging insert |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|-----------|
| 4058075214088 | Shipping box 6 | 240 mm x 240 mm x 195 mm | 3133.00 g | 11.23 dm³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

