


PRODUCT NO. 6247-099090

DOTLUX CAPPUCCINO POWERselect 30/44/74W COLORselect LED pendant luminaire



to the product page

- Stylish pendant luminaire in a modern design with the performance of a high-bay spotlight
- COLORselect in 3000K / 3500K / 4000K, suitable for every application
- With two separate power supply units, the CAPPUCCINO (art. no. 6247-099090) has a POWERselect function using phase switching.
- This means that the power level of the luminaire can be conveniently switched even at high installation heights and is also perfect for use in places where different amounts of light are required at different times
- Versatile use in stores, lounges, storage rooms, etc.
- Sturdy polycarbonate reflector included
- Suitable for VDU workstations thanks to UGR <19
- Cable length 1.5 meters

PRODUCT GROUP

EC001743_Pendelleuchte

WEIGHT IN KG	2.118
POWER CONSUMPTION IN WATTS	30/44/74
NET LUMINOUS FLUX IN LUMENS	4200/6160/10360
LUMEN PER WATT	140

Dimensions

height: 287mm
diameter: 330mm
length: 330mm
width: 330mm

PROTECTION CLASS (IP)	IP20
LIGHT COLOR	white
SERVICE LIFE	approx. 50.000 h at 25°C
COLOR TEMPERATURE IN KELVIN	3000/3500/4000
COLOR-RENDERING-INDEX	CRI > 82
POWER FACTOR	0,9
INRUSH CURRENT IN A	0
LUMEN PER WATT	140
PROTECTION CLASS	I
VOLTAGE TYPE	AC/DC
HOUSING COLOUR	white
SUITED FOR EMERGENCY LIGHTING	yes
GLARE-FREE	UGR < 19
WARRANTY IN YEARS	5
L80/B10	50000
RATED CURRENT	0.03
DIMMING WITHOUT DIMMER	No
ENABLED LICENSED PRODUCT	Yes
ASSORTMENT	Proline
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
LIFETIME L80/B10 AT 25°C	50000
LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C	100000
WITH ILLUMINANT	Yes

SUITABLE FOR LIGHT LINE CONFIGURATION	No
SUITABLE FOR WORKPLACE ACCORDING TO EN 12464-1	Yes
SUITABLE FOR NUMBER OF LIGHT SOURCES	1
LAMP HOLDER	-
MATERIAL COVER	Plastic, transparent
TYPE OF CONTROL GEAR	LED operating device current-controlled
WITH CONTROL GEAR	Yes
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	Yes
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
NO DIM FUNCTION	No
LIGHT DISTRIBUTOR	Reflector
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
DEGREE OF PROTECTION (NEMA)	1
IMPACT STRENGTH	IK06
LUMINAIRE WITH LIMITED SURFACE TEMPERATURE, SIGN "D" ACCORDING TO EN 60598-2-24	Yes
SUITABLE FOR EMERGENCY LIGHTING	Yes
WITH MOVEMENT SENSOR	No
FILAMENT TEST ACCORDING TO IEC 60695-2-11	550 °C - 30 s
CONSTANT LIGHT OUTPUT (CLO)	Yes
TYPE OF WIRING	Ending
COLOUR OF LIGHT ADJUSTABLE	Positions
LUMINOUS FLUX ADJUSTABLE	Positions
OPERATION BY BLUETOOTH	No
COMPATIBLE WITH CASAMBI	No
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
IFTTT SUPPORT AVAILABLE	No
DIRECT-/INDIRECT PROPORTION SEPARATELY CONTROLLABLE	No
EXCHANGEABLE CONTROL GEAR	Yes
SUITABLE FOR LAMP POWER IN W	-
LAMP TYPE	LED not exchangeable
WITH SUSPENSION	Yes

EMERGENCY POWER SUPPLY INTEGRATED	No
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
LIFETIME L70/B50 AT 25°C	100000
LIFETIME L90/B10 AT 25°C	25000
BEG FUNDING	only relevant in Germany
ENERGY EFFICIENCY CLASS OF THE LIGHT SOURCE OF A LUMINAIRE	C
ELDAS-NR.	941014139
DIAMETER IN MM	330
MAX. SYSTEM POWER IN W	74
ABMESSUNGEN BREITE MM	330
ABMESSUNGEN HÖHE MM	287
NOMINAL VOLTAGE IN V	230
MAX. NUMBER OF LIGHTS PER MINIATURE CIRCUIT BREAKER B16	37
MAX. NUMBER OF LIGHTS PER CIRCUIT BREAKER C16	62
EINGANGSSPANNUNG	186 - 240 AC/DC
ABSTRAHLWINKEL	90
LIGHT OUTLET	Direct
BEAM ANGLE ADJUSTABLE	No
LIGHT SHARING	Symmetric
REFLECTOR	Other
TYPE OF GRID	None
CONNECTION TYPE	Other