



## Connectors System AC 164 Plug and Socket Connectors Flat Version

### AC 164 STF/ 5 white

Plug, 5 pole, white, Coding: 1 (Mains), Cable Diameter min.: 6.5 mm, Cable Diameter max.: 11.5 mm, Voltage Rating: 240/400 V, Current Rating: 16.0 A, Cross-Section: 1.5 mm<sup>2</sup>, Connection Type: Screw



#### Order Info

<b>Reference Number (ref. no.)</b>	146455
<b>Applications</b>	Lighting, Installation, Electrical Appliances
<b>PU</b>	100
<b>EAN</b>	4028012117222

#### Type

<b>Type</b>	Plug
<b>Number of poles</b>	5 pole
<b>Clamping Units per Pole</b>	1
<b>Colour</b>	white
<b>Coding</b>	1 (Mains)
<b>Cross-Section</b>	1.5 mm <sup>2</sup>
<b>Connection Type</b>	Screw
<b>PE Function</b>	yes
<b>Protection Against Incorrect Plugging</b>	yes
<b>Latch</b>	yes

#### Technical Data

<b>Voltage Rating</b>	240/400 V
<b>Current Rating</b>	16.0 A
<b>Insulating Material</b>	PA 6.6
<b>Contact Material</b>	Brass
<b>Core Cross-Section min.</b>	0.5 mm <sup>2</sup>
<b>Core Cross-Section max.</b>	1.5 mm <sup>2</sup>
<b>Impulse Voltage Rating</b>	4.0 kV
<b>Flammability Rating</b>	V-2
<b>max. Ambient Temperature Operation</b>	70 °C
<b>IP Code</b>	IP20
<b>IP Code when Plugged</b>	IP40
<b>Type of Conductor Solid</b>	yes
<b>Type of Conductor Flexible</b>	yes

<b>Type of Conductor Stranded</b>	yes
<b>Stripping Length</b>	7.0 mm
<b>Assembly Contact Screw</b>	PZ 1 / ⚡ 0.5 Nm
<b>Assembly Strain Relief</b>	PZ 1 / ⚡ 0.5 Nm
<b>Cable Diameter min.</b>	6.5 mm
<b>Cable Diameter max.</b>	11.5 mm
<b>Approbation EN61535</b>	AC 164_EN61535_20190125_DEKRA_ENEC_71-107174_web.pdf
<b>Approbation UL</b>	160_163_AC164_AC166_20011003_20170727_UL_E220480_Sec.1-(