

OVE Austrian Electrotechnical Association
Eschenbachgasse 9, 1010 Wien, Austria
ZVR: 327279890 | DVR: 1055887 | www.ove.at

OVE Testing & Certification
Kahlenberger Str. 2A, 1190 Wien, Austria
T +43 1 370 58 06 | F +43 1 370 58 06-199



ENEC Certification Body registered under ID # 11.

Validity of ENEC Licences can be checked at www.enec.com

LICENCE

to use the European Mark



Licence No. **7590-226**

Date of issue: Wien, 2018 02 19

OVE the Austrian Electrotechnical Association as signatory to the "**Agreement on the use of a commonly agreed Mark of Conformity for certain electrical equipment complying with European Standards**" hereby grants the right to label the products mentioned hereunder and listed in the Annex with the Mark(s) shown above to the following company

Licenceholder: **Tridonic GmbH & Co KG**
Färbergasse 15
6851 Dornbirn
Austria

Product: **Electronic control gears for LED-modules**

Trade Mark: **TRIDONIC**

Series/Type: **LCI ... o4a sl PRE ...**

Basis for this given right is the conformity of the products with the requirements of the relevant Standard(s) as listed in the Annex and the fulfilment of articles 8 and 9 of the ENEC-Agreement by the manufacturer. This licence refers to the tested specimen and to all products manufactured strictly identical to the submitted one.

This licence has been issued under the presumption and conditional on the fact that the licensee holds all necessary legal rights with regard to the product presented for testing and certification.

Österreichischer Verband für Elektrotechnik
Head of Testing & Certification

Digitally signed by W. Martin
Email=w.martin@ove.at
Dipl.-Ing. W. Martin



OVE Testing & Certification

Accredited by the Federal Ministry of Science, Research and Economy as Certification Body for products within the scope as given in the official decree and published under www.en.bmwf.gv.at/accreditation



<p><i>Hersteller</i> <i>Manufacturer</i></p>	<p>Tridonic GmbH & Co KG Färbergasse 15 6851 Dornbirn Austria</p>
<p><i>Fertigungsstätte(n)</i> <i>Factory location(s)</i></p>	<p>Tridonic GmbH & Co KG Färbergasse 15 6851 Dornbirn Austria</p>
<p><i>Typenbezeichnung</i> <i>Type reference</i></p>	<p>LCI 100/200-850/300 o4a sl PRE, LCI 150/325-1050/300 o4a sl PRE, LCI 150/325-1050/300 o4a sl PRE mod see page 4</p>
<p><i>Prüfbericht</i> <i>Test Report</i></p>	<p>TGM-VA EE 35479f ECS-1/ECS-2, TGM-VA EE 35479g ECS-1/ECS-2</p>
<p><i>Nationale Bestimmung(en)</i> <i>National Standard(s)</i></p>	<p>OVE EN 61347-1:2016-06-01 OVE EN 61347-2-13:2017-11-01 ÖVE/ÖNORM EN 62384:2010-05-01</p>
<p><i>Europannorm(en)</i> <i>European Standard(s)</i></p>	<p>EN 61347-1:2015 EN 61347-2-13:2014 + A1:2017 EN 62384:2006 + A1:2009</p>
<p><i>Ersatz für Zertifikat</i> <i>Superseded licence</i></p>	<p>--</p>
<p><i>Anmerkung(en)</i> <i>Remark(s)</i></p>	<p>Complies with the additional requirements for emergency lighting according Annex J of EN 61347-2-13:2014+A1:2017.</p> <p>WMT-procedure.</p>



<i>Nennspannung</i> <i>Rated voltage</i>	AC 220-240 V, 50/60 Hz; DC 220-240 V
<i>Nennstrom (sec.)</i> <i>Rated current (sec.)</i>	see page 4
<i>Höchste Ausgangsspannung</i> <i>Max. output voltage</i>	350 V
<i>Nennleistung</i> <i>Rated power</i>	see page 4
<i>Max. Betriebstemperatur t_c</i> <i>Rated max. operating temperature t_c</i>	see page 4
<i>Umgebungstemperatur t_a</i> <i>Rated ambient temperature t_a</i>	see page 4
<i>Maximale Gehäusetemperatur</i> <i>Rated maximum case temperature</i>	110°C
<i>Kurzschlußschutz</i> <i>Short-circuit protection</i>	Short circuit proof control gear
<i>Klassifikation</i> <i>Classification</i>	Built-in electronic controlgear for LED modules, constant current type

TRADEMARK / TYPECODE		Rated output current		Maximum output voltage (no-load)		Rated output power		Rated max. operating temperature (tc)		Maximum ambient temperature (ta)		Maximum case temperature		Circuit power factor (230V, 50Hz, full load)		Case	
		[mA]	[V]	[W]	[°C]	[°C]	[°C]	[°C]	[°C]	[°C]	[°C]	[°C]	λ	Metall (M)	Plastic (P)		
1	LCI 100/200-850/300 o4a si PRE	200-850	350	100	80	70	110	0,98	M								
2	LCI 150/325-1050/300 o4a si PRE	325-1050	350	150	80/85 ¹	70	110	0,98	M								
3	LCI 150/325-1050/300 o4a si PRE mod	325-1050	350	150	70	50	110	0,98	M								

¹ Depending on output power, see marking on product or datasheet.