

Sensor-switched LED floodlight

Spot DUO

Sensor Connect

EAN 4007841 058654

Article number 058654



LED

20.000 h

3000 K

3000K
warm-white



38°



2x Infrared sensor
90°



max. 10 m



IP44



2 - 2000 lux (via
App)



manual override
4h



energy saving

3 years

manufacturer's
warranty
steinel.de/garantie3y

Function description

Excellent design. Intelligent technology. Turning through 180° and tilting through 90°, the LED double spot's two spotlight heads (2x 520 lm) provide 3000 K warm-white light. Wirelessly interconnectable by Bluetooth and adjustable and controllable via free app (twilight, time, lighting groups). Two 90° infrared sensors reliably monitor the surrounding area. Included lamp.

Spot DUO


Sensor Connect
 EAN 4007841 058654
 Article number 058654

Technical specifications

Dimensions (L x W x H)	175 x 247 x 98 mm
Mains power supply	220 – 240 V / 50 – 60 Hz
Sensor Technology	passive infrared
Output	14,6 W
Interconnection	Yes
Vernetzung via: Connect Bluetooth Mesh	Bluetooth
Slave modeselectable	Yes
Lichtstrom Gesamtprodukt	1024 lm
Efficiency (without shade/diffuser)	74 lm/W
Gesamtprodukt Effizienz	68,5 lm/W
Colour temperature	3000 K
Colour variation LED	SDCM5
Colour Rendering Index	80-89
With lamp	Yes, LED lamp
Lamp	LED can be replaced
Base	GU10
With motion detector	Yes
Detection angle	90 °
Angle of aperture	90 °
Capability of masking out individual segments	No
Electronic scalability	No
Mechanical scalability	No

Reach, radial	r = 2 m (3 m ²)
Reach, tangential	r = 10 m (79 m ²)
Continuous light	selectable, 4h
Photo-cell controller	Yes
Twilight setting	2 – 2000 lx
Time setting	5 s – 60 Min.
Basic light level function	No
Main light adjustable	No
Functions	Timer, Master/slave override
Soft light start	No
Impact resistance	IK03
IP-rating	IP44
Protection class	II
Ambient temperature	-20 – 40 °C
Housing material	Aluminium
Cover material	Plastic, transparent
Manufacturer's Warranty	3 years
Settings via	Bluetooth
Installation site	wall
Version	Sensor Connect
PU1, EAN	4007841058654

Detection Zone



Mögliche Montagehöhe: 1,80 m – 2,50 m
 Orange: radial
 Schwarz: tangential

Dimension Drawing

