

LED floodlight without sensor - Professional Line

XLED PRO 240

V2 Anthracite

EAN 4007841 068080

Article number 068080



LED

30 years (Ø 4,5h / day)

3000 K

3000K warm-white



IP44



networkable via cable



energy saving

5 years

manufacturer's warranty
steinel-professional.de/garantie



ENEC 05



KEMA KEUR



Light source not exchangeable

Function description

Day-bright illumination throughout: the XLED PRO 240 outdoor floodlight without motion detector. With fully swivelling LED flat panel and opal diffuser. 2124 lm, 3000 K, 19,3 W. Available in black, white and anthracite.

Technical specifications

Dimensions (L x W x H)	161 x 180 x 199 mm
Mains power supply	220 – 240 V / 50 – 60 Hz
Output	19,3 W
Interconnection	No
Luminous flux total product	2124 lm
Total product efficiency	110 lm/W
Colour temperature	3000 K
Colour variation LED	SDCM3
With lamp	Yes, STEINEL LED system
Lamp	LED cannot be replaced
Service life LED L70B50 (25°)	> 60000 h
Base	without
LED cooling system	HCMC (High Conductive Magnesium Composite)
With motion detector	No

Basic light level function	No
Main light adjustable	No
Soft light start	No
Impact resistance	IK03
IP-rating	IP44
Protection class	II
Ambient temperature	-20 – 40 °C
Housing material	HCMC
Cover material	Plastic, opal
Manufacturer's Warranty	5 years
Installation site	wall, corner
Version	Anthracite
PU1, EAN	4007841068080


XLED PRO 240

V2 Anthracite

EAN 4007841 068080

Article number 068080

Dimension Drawing



Master/slave interconnection circuit diagram

