



AspiraVision Compact for CDM

HID-AV C 35-70 /I CDM 220-240V 50/60Hz

AspiraVision is the mark of excellence in HID electronic gear technology – high-end, compact, lightweight and easy to use, with added features for optimal performance of 35, 50 and 70 W CDM lamps. The recently added switching function provides maximum flexibility for users by integrating three different wattage choices into a single driver.

Product data

General Information		Electrical	
Application Code	-	Inrush Current Width	10 ms
Lamp Type	CDM	Lamp Power Tolerance	-3%/+3%
Number of Lamps	1 piece/unit	Inrush Current Peak (Max)	8 A
Suitable For Outdoor Use	No	Efficiency at full load [%]	90.68 %
Number of Products on MCB (16A Type B) (Nom)	58	Wiring	
Automatic Restart	Yes	Cable Capacity Output Wires Mutual (Nom)	160 pF
		Cable Length From Device to Lamp	2 m
		Wire Striplength	10.0-11.0 mm
		Ballast Contact Wire Cross Section	0.75-2.50 mm ²
		Connector Type	WAGO series 804
Operating and Electrical		System characteristics	
Input Voltage	220 to 240 V	Rated Ballast-Lamp Power	35-70 W
Input Frequency	50 to 60 Hz	Lamp Power on CDM	39-73 W
Minimum Mains Voltage Operation (Min)	198 V	Power Loss on CDM	5-7 W
Power Factor 100% Load (Nom)	0.95	Temperature	
Ignition Voltage (Max)	5.0 kV	T-Ambient (Max)	45 °C
Ignition Voltage (Min)	3.0 kV	T-Ambient (Min)	-20 °C
Ignition Switch-Off Time (Nom)	19 min		
Mains Voltage Performance (AC)	198-254V		
Mains Voltage Safety (AC)	180-264V		
Earth Leakage Current (Max)	250 mA		

AspiraVision Compact for CDM

T-Storage (Max)	80 °C
T-Storage (Min)	-25 °C
T-Case Lifetime (Nom)	80 °C

Controls and Dimming

Control Interface	-
-------------------	---

Mechanical and Housing

Housing	/I
---------	----

Approval and Application

Surge Protection (Common/Differential)	EN61547 (L-L 2kV, L-G 4kV) kV
IP Classification Luminaire	Not Specified
Overvoltage Protection 400Vac	5 min
Active Temperature Protection	No
EMI 9 kHz ... 300 MHz	CISPR 15 ed 7.2
Safety Standard	EN 61347-2-12 and 2-1
Harmonic Current Emission Standard	IEC 61000-3-2
Vibration Standard	IEC68-2-6 F c
Bumps Standard	IEC 68-2-29 Eb



Humidity Standard	IEC 60928 clause 13
Approval Marks	EMC HEE F-Marking CE marking ENEC certificate VDE certificate CB Certificate VDE marking C-Tick certificate China Quality Certificate

Hum And Noise Level	20 dB(A)
---------------------	----------

Product Data

Full product code	871829123312100
Order product name	HID-AV C 35-70 /I CDM 220-240V 50/60Hz
EAN/UPC - Product	8718291233121
Order code	913700684066
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12
Material Nr. (12NC)	913700684066
Net Weight (Piece)	0.330 kg

Dimensional drawing



HID-AV C 35-70 /I CDM 220-240V 50/60Hz

Product	D1	C1	A1	A2	B1
HID-AV C 35-70 /I CDM 220-240V 50/60Hz	4.8 mm	34.7 mm	189.2 mm	170.7 mm	83.5 mm

