



HF-Performer III for TL-D lamps

HF-P 218/236 TL-D III 220-240V 50/60 Hz

HF-Performer III TL-D III ballasts offer maximum versatility and meet all of the necessary commercial grade specifications. They also offer the added benefits of lamp striation reduction technology, making these ballasts compatible with energy-saving lamps. As such, these ballasts are part of an overall high-efficiency lighting system that may help you or your customers to achieve any international or local energy code you need to comply with. HF-Performer III TL-D III ballasts are the ideal choice for a broad range of new construction and retrofit applications within the commercial sector, including general surface mounting or office lighting, parking garages, warehouses, waterproof and other applications.

Product data

| General Information | | | |
|--|------------------|--------------------------------|-----------|
| Application Code | III | Crestfactor (Max) | 1.7 |
| Type Version | IDC | Power Factor 100% Load (Nom) | 0.99 |
| Lamp Type | TL-D | Ignition Time (Max) | 0.9 s |
| Number Of Lamps | 2 piece/unit | Mains Voltage Performance (AC) | -8%+6% |
| Number Of Products On MCB (16A Type B) (Nom) | 28 | Mains Voltage Safety (AC) | -10%+10% |
| Automatic Restart | Yes | Earth Leakage Current (Nom) | 0.5 mA |
| | | Inrush Current Width | 0.25 ms |
| Operating and Electrical | | Constant Wattage Deviation | -2%/+2% |
| Input Voltage | 220 to 240 V | Ballast Factor (Nom) | 1 |
| Input Frequency | 50 to 60 Hz | Power Losses (Nom) | 3.2-4.9 W |
| Operating Frequency (Nom) | 45 kHz | Inrush Current Peak (Max) | 18 A |
| Ignition Method | Programmed Start | | |

HF-Performer III for TL-D lamps

| Wiring | |
|---|--|
| Connector Type Input Terminals | WAGO 251 universal connector [Suitable for both automatic wiring (ALF and ADS) and manual wiring] |
| Cable Capacity Output Wires Mutual (Nom) | 200 pF |
| Connector Type Output Terminals | WAGO 251 universal connector [Suitable for both automatic wiring (ALF and ADS) and manual wiring] |
| Cable Length Hot Wiring | 0.75 m |
| Wire Striplength | 8.0-9.0 mm |
| Dual Fixture Master/Slave | Not applicable [Master/Slave oper. not applicable] |
| Input Terminal Cross Section | 0.50-1.00 mm ² |
| Output Terminal Cross Section | 0.50-1.00 mm ² |
| Cable Capacity Output Wires To Earth (Nom) | 200 pF |
| System characteristics | |
| Rated Ballast-Lamp Power | 36/18 W |
| Rated Lamp Power On TL-D | 36/18 W |
| System Power On TL-D | 69.3/38.7 W |
| Lamp Power On TL-D | 64.4/35.5 W |
| Power Loss On TL-D | 4.9/3.2 W |
| Rated Lamp Power On PL-L | 36 W |
| System Power On PL-L | 67.5 W |
| Lamp Power On PL-L | 63.3 W |
| Power Loss On PL-L | 4.2 W |
| Temperature | |
| T-Ambient (Max) | 60 °C |
| T-Ambient (Min) | -25 °C |
| T-Storage (Max) | 50 °C |
| T-Storage (Min) | -40 °C |
| T-Case Lifetime (Nom) | 80 °C |
| T-Case Maximum (Max) | 80 °C |
| T-Ignition (Max) | 60 °C |
| T-Ignition (Min) | -25 °C |
| Mechanical and Housing | |
| Housing | L 280x30x28 |
| Emergency Operation | |
| Nominal Light Output After 60 Seconds | 100% of EBLF |
| Battery Voltage Lamp Ignition | 186-275 V |
| Normal Operating Voltage (DC) | 220-240 V |
| Battery Voltage Lamp Operation | 186-275 |
| Battery Voltage Guaranteed Operation | 176-275 V |
| Battery Voltage Guaranteed Ignition | 186-275 V |
| Emergency Ballast Lumen Factor (EBLF) (Nom) | 0.7 % |
| Nominal Light Output After 5 Seconds | 50% of EBLF |
| Approval and Application | |
| Energy Efficiency Index | A2 BAT |
| EMI 9 kHz ... 30 MHz | EN55015 |
| EMI 30 MHz ... 1000 MHz | EN55022 level B |
| Safety Standard | IEC 61347-2-3 |
| Performance Standard | IEC 60929 |
| Quality Standard | ISO 9000:2000 |
| Environmental Standard | ISO 14001 |
| Harmonic Current Emission Standard | IEC 61000-3-2 |
| EMC Immunity Standard | IEC 61547 |
| Vibration Standard | IEC68-2-6 F c |
| Bumps Standard | IEC 68-2-29 Eb |
| Humidity Standard | EN 61347-2-3 clause 11 |
| Approval Marks | CE marking ENEC certificate VDE-EMV certificate |
| Temperature Marking | Yes |
| Emergency Standard | IEC 60598-2-22 |
| Hum And Noise Level | < 30 dB(A) |
| Product Data | |
| Full product code | 872790091166400 |
| Order product name | HF-P 218/236 TL-D III 220-240V 50/60 Hz |
| EAN/UPC - Product | 8711500999665 |
| Order code | 913713031666 |
| Numerator - Quantity Per Pack | 1 |
| Numerator - Packs per outer box | 12 |
| Material Nr. (12NC) | 913713031666 |
| Net Weight (Piece) | 0.203 kg |

HF-Performer III for TL-D lamps

Dimensional drawing

| Product | D1 | C1 | A1 | A2 | B1 |
|---|--------|---------|----------|----------|---------|
| HF-P 218/236 TL-D III 220-240V 50/60 Hz | 4.2 mm | 28.0 mm | 280.0 mm | 265.0 mm | 30.0 mm |

HF-P 218/236 TL-D III 220-240V 50/60Hz

Photometric data

