

PRODUCT DATASHEET Linear LED Flat 6 W/3000 K

LinearLED Flat® | Slim undercabinet luminaire for surface mounting

Areas of application

- Undercabinet lighting



Product benefits

- Connection of up to 43 (ECO version) or 18 (sensor Version) luminaires in a row
- Various accessories included: cables and connectors



TECHNICAL DATA

Electrical data

Nominal wattage	6.00 W
Nominal voltage	220240 V
Mains frequency	5060 Hz
Nominal current	40 mA
Power factor λ	> 0.5
Protection class	Ш

Photometrical data

Luminous flux	300 lm	
Total luminous flux of contained light sources	1430 lm	
Luminous efficacy	64 lm/W	
Color temperature	3000 К	
Light color (designation)	Warm White	
Color rendering index Ra	> 80	
Beam angle	120 °	

Dimensions & Weight

Length	370.00 mm
Width	67.00 mm
Height	22.00 mm
Product weight	325.00 g



Materials & Colors

Product color	Silver
Housing color	Silver
Body material	Aluminum
Cover material	Polycarbonate (PC)
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20+40 °C	
Type of connection	Plug type C (EU)	
Type of protection	IP20	
Dimmable	No	
Mounting type	Surface	
Mounting location	Cabinet undersides	
Application environment	Indoor	
LED module replaceable	Not replaceable	

Lifespan

Number of switching cycles 100000

Certificates & Standards

Standards

CE / EAC / REACH / RoHS

DOWNLOAD DATA

	DOWNLOAD DATA
PDF	User instruction
1	Tender documents
PDF	Declarations of conformity
PDF	Packaging insert

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075264151	Shipping box 8	425 mm x 334 mm x 93 mm	3706.00 g	13.20 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.