

PRODUCT DATASHEET

SMART+ WIFI PLUG EU

SMART+ Plug | Plug with smart socket to control non-smart devices with WiFi technology, pairable with Remote Controller



Areas of application

- Wherever non-smart devices need to be integrated into compatible smart home systems

Product benefits

- Integrates conventional electric equipment into compatible smart home systems
- Enables switching of conventional light sources and other electric devices remotely
- Simple connection of electric devices via standard socket
- Monitors energy usage of connected devices and tracks the energy consumption

Product features

- Controllable via LEDVANCE SMART+ WiFi App (with minimum Android™ 4.4 or iOS 9.0)
- Controllable via LEDVANCE SMART+ WiFi Remote Controller
- High switching power: up to 2.300 W / 10 A
- Network protocol: WiFi
- Energy meter
- Scheduling
- Voice control works with Hey Google or Alexa




TECHNICAL DATA

Electrical data

Nominal voltage	230 V
Operating frequency	50 Hz
Mains frequency	50 Hz

Dimensions & Weight



Product weight	97.00 g
Length	80.0 mm
Width	49 mm
Height	59 mm

Lifespan

Number of switching cycles	100000
Lifespan	25000 h

Colors & materials

Product color	White
Body material	Plastic
Cover material	Plastic

Temperatures & operating conditions

Ambient temperature range	-10...+35 °C
---------------------------	--------------

Certificates & Standards

Standards	CE
Protection class	I
Type of protection	IP20



EQUIPMENT / ACCESSORIES

- For control via LEDVANCE SMART+ WiFi App, a smart phone or Tablet PC is required (with minimum Android 4.4 or iOS 9.0)

Safety advice

- Disconnect devices which generate heat from the mains, i.e. from the LIGHTIFY® Plug, after use in order to avoid them being accidentally switched on.
- Very high capacitive and inductive loads may in some cases lead to destruction of the device or reduction in the number of switching cycles.
- Do not use the SMART+ Outdoor Plug in conjunction with medical equipment.
- To be connected to an automatic circuit breaker (max. 16 A).

DOWNLOAD DATA

DOWNLOAD DATA	
	Declarations of conformity
	Installation guide

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075537255	Shipping box 4	173 mm x 108 mm x 141 mm	642.00 g	2.63 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.