



68A40101-0062

series: Schutzrohrleuchten LED Tube lights

Type of installation: universal mounting system
 Type of Protection: IP 67
 Protection Class: I
 Lamp: LED
 Dimensions: D 120, L 1310
 Colour: grey

Protective tube plastic opal (polycarbonate), end caps plastic grey (polyamide), integrated electronic driver, 2 protectors blue, socket, power supply cable with mains plug, incl. LED panel

electro-technics:

Electric Gear Converter
 System Capacity 45 W
 Voltage 220 - 240 V / 50 - 60 Hz

Spezifikationen:

Colour TPE blue
 Power supply cable H07RN-F
 Size power supply cable 3 x 1,5 mm²
 Length power supply cable 5 m
 Colour power supply cable black
 Connector systems Typ F, Schuko IP68 (CEE 7/4)
 Lamp cover opal
 Socket outlets 1

testings:

Type of Protection IP 67
 Glow Wire Test 650°C - 30 seconds
 Impact Protection IK08 (5 Joule)
 Safety Marks D-mark, F-mark
 Other Marks WEEE mark
 Protection Class I
 Energy efficiency class LED A++
 Energy efficiency class of included lamp A++

lamp 1:

Lamp LED
 Number of Lamps 4
 Wattage 10,00 W
 Socket without socket
 Colour Temperature 5000 K
 Colour rendering index (CRI) 1 80
 Lifespan

weights and measures:

Diameter D 120 mm
 Length L 1.310 mm
 Weight 3,82 kg

lighting technology:

Luminaire flux 5.300 lm

accessories

68Z00001 Mounting bracket (plastic) grey
 68Z00002 Mounting bracket (metal) with magnet verzinkt
 68Z00003 Mounting bracket (plastic) with magnet grey
 68Z00004 Mounting bracket (metal) with hanger assembly of stainless steel verzinkt
 68Z00005 Webbing suspension verzinkt
 68Z00006 Expander suspension verzinkt