



HB 710

501050.002 | Oval bulkhead luminaires

Oval bulkhead luminaires
4051859537557
LED
L 207, B 97, H 56



Oval luminaire in classic design. Housing and diffuser: opal, made of shockproof plastic (polycarbonate). Internal fixing points mean no screws are visible. Simple, tool-free installation using the Plug & Play plug-in system. LED module can be connected without use of tools. Convenient, flexible connection option using 2 rear and 4 lateral cable inlets. Suitable for through-wiring. MultiLumen: 2 steps adjustable luminous flux. Factory setting is the highest luminous flux.

Colour

Colour white

Dimensions

Length L 207 mm
Width B 97 mm
Height H 56 mm
Weight 220 g

Lamp

Lamp LED
Colour temperature 4000K
Colour rendering index (CRI) 80
Colour tolerance 4
Rated life 35000 h (L70/B50)
Photobiological safety according to EN 62471 Risk group 0

Lighting technology

Colour temperature 4.000 K
Rated luminous flux 1.100 lm
Glare evaluation UGR (4H 8H) 1 27,2
Beam angle 132° / 118°
Colour temperature 2 4.000 K
Rated luminous flux 2 700 lm
Glare evaluation UGR (4H 8H) 2 25,6
Beam angle Down 2 132° / 118°

Electrical

Control gear	EB
Voltage	220 - 240 V / 50 - 60 Hz
Luminaires on B10A fuse	38
Luminaires on B16A fuse	60
Luminaires on C10A fuse	62
Luminaires on C16A fuse	102
Inrush current / Inrush current duration	5,4 A / 160 µs
System power	9,5 W
Luminaire efficacy	116 lm/W
System power 2	6 W
Luminous efficiency 2	117 lm/W

Approbations

Type of protection	IP 54
Protection class	II
Filament test	650°C - 30 seconds
Impact resistance	IK07 (2 Joule)
Safety marks	D-mark
Ambient temperature min.	-30 °C
Ambient temperature max.	35 °C
ULOR	9,5 %
Conformity mark	CE, EAC
CIE Flux Code / CEN Flux Code	41 70 90 91 100
Energieeffizienzklasse 2019/2015	D
Non-maintained power mode	Umgebungstemperatur / temperature ambiante => -30 °C ... + 35 °C