IS 3360

V3 KNX - concealed, sq. white
EAN 4007841 058173
Article number 058173

. steinel

infrared sensor 360°	max. 20 m	KNX	IP20	2 - 1000 lux	1 - 255 min	ideal 2,5 - 4 m	Teach mode	energy saving	5 years manufacturer's warranty steinel-professional.de/garantie

Function description

Higher, further, faster. Infrared motion detector IS 3360 for indoors and out, ideal for watching over high spaces and large areas, such as multi-storey and underground car parks, installation height up to 4 m, 360° angle of coverage, reach 20 m max. (tangential). Available either in round or square surface-mounted, concealed or In-ceiling installation.

IS 3360

V3 KNX - concealed, sq. white
EAN 4007841 058173
Article number 058173

.○ steinel

Technical specifications

|			
Type	Motion and Presence Detector	Twilight setting	2 – 1000 lx
Dimensions (L x W x H)	78 x 94 x 94 mm	Time setting	5 s – 15 Min.
Power supply, detail	KNX bus	Constant-lighting control	Yes
Sensor Technology	passive infrared	Basic light level function	Yes
Application, place	Indoors	KNX functions	Photo-cell controller, Basic light level function, Light level, HVAC output, Constant-lighting control, Light output 2x, Presence output, Day / night function, Logic gate
Installation site	ceiling		
Installation	Concealed wiring		
Mounting height	2,50 – 4,00 m		
Reach, radial	Ø 8 m (50 m^2)	With bus coupling	Yes
Reach, tangential	Ø 40 m (1257 m^2)	Settings via	ETS software, Remote control, Bus, Smart Remote
Reach, presence	Ø 3 m (7 m^2)	With remote control	No
Detection angle	360 °	Interconnection	Yes
Angle of aperture	180 °	Type of interconnection	Master/slave
Switching zones	1416 switching zones	IP-rating	IP20
Optimum mounting height	2,8 m	Material	Plastic
Mechanical scalability	No	Ambient temperature	-20 – 50 °C
Sneak-by guard	Yes	Application, room	production facilities, recreation room, changing room, function room / ancillary room, sports hall, reception / lobby, stairwell, WC / washroom, multi-storey / underground car park, warehouse, Indoors
Capability of masking out individual segments	Yes		
Electronic scalability	No		
Twilight setting TEACH	Yes		
		Colour	white
		Colour, RAL	9003
		Manufacturer's Warranty	5 years
		Version	KNX - concealed, sq. white
		PU1, EAN	4007841058173

Accessories

EAN 4007841 009151	Remote control Smart Remote
EAN 4007841 593018	Service remote control RC6 KNX
EAN 4007841 592912	User remote control RC7 KNX
EAN 4007841 056728	Black cover for IR-sensors

steinel

Detection Zone

● 2,8 m

{a1695}

{a1707}

Mögliche Montagehöhe: 2,50 m – 4,00 m
Orange: radial
Schwarz: tangential

Dimension Drawing

94

94

78