

LED floodlight without sensor

Spot Way

Slave

EAN 4007841 068677

Article number 068677



LED

20.000 h

3000 K

3000K
warm-white



38°



IP44



energy saving



CE

3 years

manufacturer's
warranty
steinel.de/garantie3y



Control gear not
exchangeable

Function description

Path light with wow effect. With the 57 cm tall "Spot Way", outstanding design meets ingenious technology. The tilting and turning ground spot perfectly illuminates driveways and entrance paths with 512 lm (6,7 W). With 2.5 m power cord. Includes lamp (GU-10 LED).

Technical specifications

Dimensions (L x W x H)	226 x 140 x 572 mm
Mains power supply	220 – 240 V / 50 – 60 Hz
Output	6,7 W
Interconnection	No
Lichtstrom Gesamtprodukt	512 lm
Efficiency (without shade/diffuser)	74 lm/W
Gesamtprodukt Effizienz	76,4 lm/W
Colour temperature	3000 K
Colour variation LED	SDCM5
Colour Rendering Index	80-89
With lamp	Yes, LED lamp
Lamp	LED can be replaced
Base	GU10
With motion detector	No

Photo-cell controller	No
Basic light level function	No
Main light adjustable	No
Soft light start	No
Impact resistance	IK03
IP-rating	IP44
Protection class	II
Ambient temperature	-20 – 40 °C
Housing material	Aluminium
Cover material	Plastic, transparent
Manufacturer's Warranty	3 years
Installation site	Stand
Version	Slave
PU1, EAN	4007841068677

LED floodlight without sensor

Spot Way

Slave

EAN 4007841 068677

Article number 068677



Dimension Drawing

